# SAFETY DATA SHEET

### **Danish Oil Dark Walnut**



# **Section 1. Identification**

**GHS** product identifier

Other means of identification

: Danish Oil Dark Walnut

: Not available.

**Product type** 

: Liquid.

**Identified uses** 

Oil-based stain.

**Manufacturer** 

: General Finishes 2462 Corporate Circle East Troy, WI 53120

U.S.A.

Phone no.: 262-642-4545 Toll free no.: 1-800-783-6050 Fax no.: 262-642-4707 Web: GeneralFinishes.com

Emergency telephone number (with hours of

operation)

: CHEMTREC, U.S.: 1-800-424-9300 Inte

International: +1-703-527-3887

(24/7)

### Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 4 SKIN SENSITIZATION - Category 1

GERM CELL MUTAGENICITY - Category 1B

**CARCINOGENICITY - Category 1B** 

TOXIC TO REPRODUCTION (Fertility) - Category 2

**GHS label elements** 

Hazard pictograms





Signal word : Danger

**Hazard statements** : Combustible liquid.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility.

**Precautionary statements** 

**General** 

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.





### Section 2. Hazards identification

**Prevention**: Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from flames and hot surfaces. - No smoking. Avoid breathing vapor. Contaminated work clothing should not

be allowed out of the workplace.

**Response**: IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of

soap and water. Wash contaminated clothing before reuse. If skin irritation or rash

occurs: Get medical attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazards not otherwise

classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

### **CAS** number/other identifiers

CAS number : Not applicable.

Product code : Not available.

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light	30 - 60	64742-47-8
Light aromatic petroleum naphtha	1 - 5	64742-95-6
2-Butanone oxime	0.1 - 1	96-29-7
Naphtha (petroleum), hydrotreated heavy	0.1 - 1	64742-48-9
Cobalt bis(2-ethylhexanoate)	0.1 - 1	136-52-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

### **Description of necessary first aid measures**

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 20 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention. If unconscious, place in recovery position and get medical attention immediately.

**Skin contact** 

: Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.



### Section 4. First aid measures

### Ingestion

: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

### Most important symptoms/effects, acute and delayed

### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

**Eye contact**: No known significant effects or critical hazards.

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

quantities have been ingested or inhaled

Specific treatments : No specific treatment.
 Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)



# **Section 5. Fire-fighting measures**

### Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing** media

: Do not use water jet or water-based fire extinguishers.

Specific hazards arising from the chemical

: Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide

**Special protective actions** for fire-fighters

: Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.



# Section 7. Handling and storage

### Precautions for safe handling

#### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures. Remove contaminated clothing and protective equipment before entering eating areas.

# Conditions for safe storage, : including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated light	OSHA PEL (United States).  TWA: 213 ppm  TWA: 1200 mg/m³  ACGIH TLV (United States, 6/2013). Absorbed through skin.  TWA: 200 mg/m³, (as total hydrocarbon vapor) 8 hours.
2-Butanone oxime	AIHA WEEL (United States, 5/2010). Skin sensitizer.
Naphtha (petroleum), hydrotreated heavy	TWA: 10 ppm 8 hours.  ACGIH TLV (United States).  TWA: 300 ppm 8 hours.

# Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

### **Individual protection measures**





# Section 8. Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

**Skin protection** 

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Use a properly fitted, air-purifying or supplied air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# Section 9. Physical and chemical properties

### **Appearance**

Physical state : Liquid.

Color : Dark Walnut.

Odor : Not available.

Odor threshold : Not available.

PH : Not available.

Melting point : Not available.

Boiling point : Not available.

Flash point : Closed cup: >62°C (>143.6°F)

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.
Relative density : Not available.
Solubility : Not available.





# Section 9. Physical and chemical properties

Partition coefficient: n-

octanol/water

: Not available.

**Auto-ignition temperature** 

: Not available. **Decomposition temperature** : Not available.

**Viscosity VOC** content : Not available. : 471.124 g/L

# Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** 

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**Incompatible materials** 

: Reactive or incompatible with the following materials: oxidizing materials.

**Hazardous decomposition** products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

# Section 11. Toxicological information

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Light aromatic petroleum naphtha	LD50 Oral	Rat	8400 mg/kg	-
2-Butanone oxime	LD50 Oral	Rat	930 mg/kg	-
Naphtha (petroleum), hydrotreated	LC50 Inhalation Vapor	Rat	8500 mg/m <sup>3</sup>	4 hours
heavy	·			
	LD50 Oral	Rat	>6 g/kg	-
Cobalt bis(2-ethylhexanoate)	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	1.22 g/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Light aromatic petroleum naphtha 2-Butanone oxime	Eyes - Mild irritant Eyes - Severe irritant	Rabbit Rabbit		24 hours 100 μL 100 μL	-

#### Sensitization

There is no data available.

### Carcinogenicity

There is no data available.

### Specific target organ toxicity (single exposure)

There is no data available.

### Specific target organ toxicity (repeated exposure)

There is no data available.

### **Aspiration hazard**





# **Section 11. Toxicological information**

Name	Result
Light aromatic petroleum naphtha	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Skin contact

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

**Eye contact** : No known significant effects or critical hazards. **Inhalation** : No known significant effects or critical hazards.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contactInhalationNo known significant effects or critical hazards.Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

: May cause an allergic skin reaction.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

effects

: No known significant effects or critical hazards.

**Potential delayed effects**: No known significant effects or critical hazards.

Long term exposure

**Potential immediate** 

effects

: No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

**Carcinogenicity**: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : May cause genetic defects.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.



# **Section 11. Toxicological information**

Numerical measures of toxicity

Acute toxicity estimates

There is no data available.

# Section 12. Ecological information

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated light	Acute LC50 2200 μg/L Fresh water	Fish - Lepomis macrochirus	4 days
	Acute LC50 843000 to 914000 µg/L Fresh water	Fish - Pimephales promelas	96 hours

### Persistence and degradability

There is no data available.

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
2-Butanone oxime Naphtha (petroleum), hydrotreated	0.63	2.5 to 5.8 10 to 2500	low high
heavy Cobalt bis(2-ethylhexanoate)	-	15600	high

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.





# **Section 14. Transport information**

	DOT Classification	IMDG	IATA
UN number	NA1993	Not regulated.	Not regulated.
UN proper shipping name	COMBUSTIBLE LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Light aromatic petroleum naphtha)	-	-
Transport hazard class(es)	Combustible liquid.	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials.	-	-

**AERG**: 128

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not available.

to Annex II of MARPOL 73/78 and the IBC Code

# Section 15. Regulatory information

**U.S. Federal regulations** 

: TSCA 4(a) final test rules: Nonane

TSCA 8(a) PAIR: Nonane

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 311: Propionic acid

**Clean Air Act Section 112** 

(b) Hazardous Air **Pollutants (HAPs)**  : Listed

Clean Air Act Section 602

**Class I Substances** 

: Not listed

Clean Air Act Section 602 : Not listed

**Class II Substances** 

**DEA List I Chemicals** 

: Not listed

(Precursor Chemicals)

**DEA List II Chemicals** (Essential Chemicals) : Not listed

**SARA 302/304** 

Composition/information on ingredients





# **Section 15. Regulatory information**

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

### **Composition/information on ingredients**

Name	%		Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
Distillates (petroleum), hydrotreated light 2-Butanone oxime Naphtha (petroleum), hydrotreated heavy Cobalt bis(2-ethylhexanoate)	30 - 60 0.1 - 1 0.1 - 1 0.1 - 1	Yes. No. No. No.	No. No. No. No.	No. No. No.	No. Yes. No. Yes.	No. Yes. Yes. Yes.

### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	J	68553-15-1 136-52-7	10 - 30 0.1 - 1
Supplier notification	J	68553-15-1 136-52-7	10 - 30 0.1 - 1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### **State regulations**

Massachusetts
None of the components are listed.
New York
None of the components are listed.
New Jersey
None of the components are listed.

Pennsylvania : The following components are listed: Linseed oil, cobalt manganese salt

California Prop. 65

**WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer.

Ingredient name	Cancer	•		Maximum acceptable dosage level
Cumene	Yes.	No.	No.	No.

### **International regulations**

International lists : Australia inventory (AICS): Not determined.

China inventory (IECSC): Not determined.

Japan inventory: Not determined.

**Korea inventory**: All components are listed or exempted. **Malaysia Inventory (EHS Register)**: Not determined.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): Not determined. Taiwan inventory (CSNN): Not determined.

Chemical Weapons
Convention List Schedule

I Chemicals

: Not listed

**Chemical Weapons** 

Convention List Schedule

: Not listed

**II Chemicals** 





# **Section 15. Regulatory information**

Chemical Weapons
Convention List Schedule
III Chemicals

: Not listed

### Section 16. Other information

### **History**

Date of issue mm/dd/yyyy : 12/30/2014

Version : 1

Revised Section(s) : Not applicable.

Prepared by : KMK Regulatory Services Inc.

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

**UN = United Nations** 

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.