



PRO SERIES POLY CLEAR & WHITE



Formulated to Compete in Today's Market

General Finishes Enduro® Pro Series Polyurethane Clear and White are polyurethane/acrylic topcoats designed for fast build and 2-coat hide.

Additional features include:

- Tintable
- Fast dry
- 2-coat capability
- High film clarity
- Excellent flow & leveling
- Meet or exceed KCMA standards



Scan the QR code
for more information, or visit
gf.support/proseries-advantage.

Call toll-free at **800-783-6050**

**ENDURO® THE GOLD STANDARD FOR INDUSTRIAL &
PROFESSIONAL WATER-BASED WOOD COATINGS™**

GeneralFinishes.com



**ENDURO®**
BY GENERAL FINISHES

PRO SERIES POLY CLEAR & WHITE

08/08/23

PRODUCT CODES

Sheen	Clear	White
Flat	B824	B826
Satin	B823	B827
Semi-Gloss	B825	B828

DESCRIPTION

Interior only, Tintable,
Water-based Self-crosslinking
Polyurethane/Acrylic
Dispersion

FEATURES

- Fast dry
- Great build
- 2 coat system for certain applications
- (Pro Series Clear)
Excellent film clarity
- (Pro Series White)
Fast hide
- Excellent flow & leveling

RECOMMENDED USES

Interior cabinets, trim, doors
and furniture. Use over raw,
stained or primed wood
substrates.

PRIMING

Designed to adhere to raw &
stained wood, *Enduro White
Undercoat* & *GF Stain Blocker*.
When tinted & applied over
an existing sealed surface,
ALWAYS PRIME with *Enduro
White Undercoat* or *GF Stain
Blocker*.

COMPLIES WITH THE FOLLOWING AIR QUALITY REGULATIONS:

SCAQMD, CARB, Canada, OTC Phase I & Phase II

MEETS KCMA AND AWI SYSTEM 2 STANDARDS

PROPERTIES

Sheens Available:	Flat (10), Satin (30), Semi-Gloss (55)
Tintable:	Yes
Volume Solids:	30% - 32%, dependent on sheen
Weight Solids:	30% - 47%, dependent on sheen
Recommended Film Thickness	Wet: 3-5 mils
Average Coverage:	450 sq.ft. (41.81 m ²) per Gallon. Will vary due to mil thickness, applicator & technique.
Viscosity:	Medium (600-800 cPs)
Application:	Spray only
HVLP:	1.1mm - 1.5mm
Air-Assist Airless:	(Pro Series Clear) 300 - 300 PSI pump, (Pro Series White) 1000 - 1200 PSI pump, 20 PSI assist air, .011" - .013" tip
Airless:	Fine Finish .007" - .011"
Dry Time (touch):	30+ min.
Dry Time (recoat):	1 - 2+ hr, based on heat & airflow.
Thin with (if needed):	Water, <i>Enduro Extender</i>
Clean Hands with:	Soap & Water
Clean Equipment with:	H2O/Alcohol mixture, <i>GF Brush & Gun Cleaner</i>
Sizes Available:	Gallons, 5-gallon pails, 55-gallon drums
VOC:	Under 200 g/L.

TINTING

We recommend tinting with ColourFal Zero VOC colorants. Other
colorant systems should be zero VOC and tested thoroughly.

Complete instructions & videos at GeneralFinishes.com.

See Safety Data Sheet ("SDS") for more information on product hazards
and precautions, GeneralFinishes.com/safety.

