

General Finishes Water-Based Paint, Glaze & Pigmented Topcoat Product Comparison

Scan QR code to compare GF products.



Enduro® 2K White Poly	Enduro® White Poly	Enduro® Black Poly	Enduro® Pro Series Polyurethane White	Exterior 450 White	Milk Paint	Glaze Effects
ENDURO PERENTA PINENTE 2K WHITE POLY GLOSS / BRILL 1 Maria Control and 100 Miles 1 Maria	ENDURO IT GENERAL MINISTER WHITE POLY SATIN / SATINADO TO THE SATINATION OF THE	ENDURO BLACK POLY SATIN CATINADO WINDS GRADA MARINATION WINDS AND MARINATION WINDS	PRO SERIES POLYURETHANE WHITE FLAT MAYE	TRAINER BASED PIGMENTED TOPOGET. TERRIOR 450 WHILL FLAT	WATER BASED. MILK PAINT ANTIQUE WHITE	WATER BASED OLAZIE REFECTS PITCH BLACK BRANCESCHICK STREET OCCUPANIES OC
Interior & Exterior Tintable 2K Urethane	Interior White Enamel	Interior Black Polyurethane	Interior White, Competitively Priced	Exterior White	Interior & Exterior Flat Paint	For Creating Artistic Features
SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE
Interior & Exterior Commercial Furniture, Doors, Cabinets, Millwork, Fiberglass, Pre-Primed Steel	White Furniture, Cabinets, Millwork	Black Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork	Exterior Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork
PRODUCT COLOR	PRODUCT COLOR	PRODUCT COLOR	PRODUCT COLOR	PRODUCT COLOR	PRODUCT COLOR	PRODUCT COLOR
White, Tintable (Tintable Clear Available)	White, Tintable (Tintable Clear Available)	Black	White, Tintable (Tintable Clear Available)	White, Tintable (Tintable Clear Available)	12 Stock Colors, Clear & White Tint Bases	5 Stock Colors & Clear Tint Base
SHEEN	SHEEN	SHEEN	SHEEN	SHEEN	SHEEN	SHEEN
Flat (≤10), Satin (25-35), Semi-Gloss (50-60), Gloss (80+)	Flat (≤10), Satin (25-35), Semi-Gloss (50-60)	Satin (25-35), Semi-Gloss (50-60)	Flat (≤10), Satin (25-35), Semi-Gloss (50-60)	Flat (≤10), Satin (25-35), Semi-Gloss (50-60)	Flat Low Luster (10-15)	N/A
INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR
Interior & Exterior	Interior Only	Interior Only	Interior Only	Exterior Only, No Decks	Interior & Exterior	Interior Only
TYPE	TYPE	TYPE	TYPE	TYPE	TYPE	TYPE
Urethane	Urethane/Acrylic Blend	Urethane/Acrylic Blend	Polyurethane/Acrylic Blend	Urethane/Acrylic Blend	Acrylic Paint	Glaze
CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES
Gallons, 5-Gallon Pails	Quarts, Gallons, 5-Gallon Pails*	Gallons, 5-Gallon Pails*	Gallons, 5-Gallon Pails*	Quarts, Gallons, 5-Gallon Pails	Pints, Quarts, Gallons, 5-Gallon Pails	Pints, Quarts, Gallons
COVERAGE	COVERAGE	COVERAGE	COVERAGE	COVERAGE	COVERAGE	COVERAGE
450 Sq.Ft./Gal.	450 Sq.Ft./Gal.	450 Sq.Ft./Gal.	450 Sq.Ft./Gal.	450 Sq.Ft./Gal.	400-500 Sq.Ft./Gal.	480-640 Sq.Ft./Gal.
COATS	COATS	COATS	COATS	COATS	COATS	COATS
2-3 Coats	2-3 Coats	3 Coats	1-3 Coats	2-3 Coats	1+ Coats	1+ Coats
APPLICATION	APPLICATION	APPLICATION	APPLICATION	APPLICATION	APPLICATION	APPLICATION
Spray	Spray	Spray	Brush, Roll, Spray	Brush, Roll, Spray	Brush, Roll, Spray, Pad	Brush, Spray
OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES
Yes	Yes	Yes	Yes	Yes	Yes	Yes
TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE
HVLP 1.1mm-1.3mm	HVLP 1.3mm-1.5mm	HVLP 1.3mm-1.5mm	HVLP 1.1mm-1.5mm	HVLP 1.1mm-1.5mm	HVLP 1.8mm-2.0mm	HVLP 1.3mm-2.0mm
DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH
30+ Min.	30+ Min.	30+ Min.	30+ Min.	30+ Min.	30+ Min.	1+ Hr.
DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT
1+ Hr.	1+ Hr.	1+ Hr.	1+ Hr.	2+ Hr.	2+ Hr.	3+ Hr.
DURABILITY	DURABILITY	DURABILITY	DURABILITY	DURABILITY	DURABILITY	DURABILITY
Highest	High	High	Medium	High	High	N/A
VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY
Medium	Medium	Medium	Medium	Medium	Thick	Medium
WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS
46%	45%	31%	47%	46%	54%	22%
VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS
35%	33%	28%	35%	35%	47%	N/A
VOC	voc	Voc	Voc	Voc	voc	Voc
<200 g/L	<250 g/L	<255 g/L	<150 g/L	<140 g/L	<50 g/L	<275 g/L



