SAFETY DATA SHEET

Floor Stain White



Section 1. Identification

GHS product identifier : Floor Stain White

Code Other means of : Not available. : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

: Not available. **Identified uses**

: General Finishes Manufacturer

> 2462 Corporate Circle East Troy, WI 53120

U.S.A.

Phone no.: 262-642-4545 Toll free no.: 1-800-783-6050 Fax no.: 262-642-4707 Web: GeneralFinishes.com

Emergency telephone number (with hours of operation)

: CHEMTREC, U.S.: 1-800-424-9300 International: +1-703-527-3887

(24/7)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the : CARCINOGENICITY - Category 2

AQUATIC HAZARD (ACUTE) - Category 3 substance or mixture AQUATIC HAZARD (LONG-TERM) - Category 3

GHS label elements

Hazard pictograms



Signal word : Warning

Hazard statements : H351 - Suspected of causing cancer.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.

P273 - Avoid release to the environment.

: P308 + P313 - IF exposed or concerned: Get medical attention. Response

Storage : P405 - Store locked up.





Section 2. Hazards identification

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not : None known. result in classification/ HHNOC/PHNOC

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

CAS number/other identifiers

: Not applicable. **CAS** number **Product code** : Not available.

Ingredient name	%	CAS number
Titanium dioxide	≥10 - ≤20	13463-67-7
Propane-1,2-diol	≥5 - ≤5.5	57-55-6
Silicon dioxide	≥1 - ≤2	7631-86-9
Poly(oxy-1,2-ethanediyl), α -[4-(1,1,3,3-tetramethylbutyl)phenyl]- ω -hydroxy-	≥1 - ≤1.5	9002-93-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 20 minutes. Get medical attention.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately.

Skin contact

: Flush contaminated skin with plenty of water. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Most important symptoms/effects, acute and delayed

Potential acute health effects

: No known significant effects or critical hazards. Eye contact Inhalation No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.





Section 4. First aid measures

Over-exposure signs/symptoms

Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products : This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide metal oxide/oxides

Special protective actions for fire-fighters

Special protective equipment for fire-fighters : No special measures are required.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".



Section 6. Accidental release measures

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters
United States

Occupational exposure limits



Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Titanium dioxide	ACGIH TLV (United States, 3/2015).
	TWA: 10 mg/m³ 8 hours.
	OSHA PEL (United States, 2/2013).
	TWA: 15 mg/m³ 8 hours. Form: Total dust
Propane-1,2-diol	AIHA WEEL (United States, 10/2011).
	TWA: 10 mg/m³ 8 hours.
Silicon dioxide	NIOSH REL (United States, 10/2013).
	TWA: 6 mg/m³ 10 hours.
Poly(oxy-1,2-ethanediyl), α -[4-(1,1,3,3-tetramethylbutyl)phenyl]- ω -hydroxy-	None.

Canada

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 10 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 5/2015). TWA: 3 mg/m³ 8 hours. Form: Respirable dust TWA: 10 mg/m³ 8 hours. Form: Total dust CA Ontario Provincial (Canada, 7/2015). TWA: 10 mg/m³ 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 10 mg/m³ 8 hours. Form: Total dust CA Saskatchewan Provincial (Canada). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours.
Propane-1,2-diol	CA Ontario Provincial (Canada, 7/2015). TWA: 10 mg/m³ 8 hours. Form: Aerosol only TWA: 155 mg/m³ 8 hours. Form: Vapor and aerosol TWA: 50 ppm 8 hours. Form: Vapor and aerosol

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.



Section 8. Exposure controls/personal protection

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Fluid.]

Color : White.

Odor Not available. **Odor threshold** : Not available.

pН : 8 to 9

Melting point : Not available. **Boiling point** : Not available. Not available. Flash point : Not available. **Evaporation rate** Flammability (solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available. Vapor density : Not available.

1.21 Relative density

Soluble in the following materials: cold water and hot water. Solubility

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature Not available. **Decomposition temperature** : Not available. **Viscosity** : Not available. **VOC** content : 141.690 g/L

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Do not freeze.

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials.





Section 10. Stability and reactivity

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
	LD50 Dermal LD50 Oral		20800 mg/kg 20 g/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Propane-1,2-diol	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Mild irritant	Rabbit	-	100 mg	-
Silicon dioxide	Eyes - Mild irritant	Rabbit	-	24 hours 25 mg	-
Poly(oxy-1,2-ethanediyl), α -[4-(1,1,3,3 -tetramethylbutyl)phenyl]- ω -hydroxy-	Eyes - Moderate irritant	Rabbit	-	24 hours 10 μL	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 μL	-

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP	ACGIH	EPA	NIOSH
Titanium dioxide	-	2B	-	A4	-	+
Silicon dioxide	-	3	-	-	-	-
Aluminium hydroxide	-	-	-	A4	-	-

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

There is no data available.

Information on the likely routes of exposure

: Dermal contact. Eye contact. Ingestion.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.





Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate

effects

: No known significant effects or critical hazards.

Potential delayed effects: No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	26910.7 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide	Acute LC50 3 mg/L Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/L Fresh water	Daphnia - Daphnia pulex - Neonate	48 hours
	Acute LC50 >1000000 µg/L Marine water	Fish - Fundulus heteroclitus	96 hours
Propane-1,2-diol	Acute EC50 >110 ppm Fresh water	Daphnia - Daphnia magna	48 hours
•	Acute LC50 1020000 µg/L Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 710000 µg/L Fresh water	Fish - Pimephales promelas	96 hours
Poly(oxy-1,2-ethanediyl), α -[4-(1,1,3,3 -tetramethylbutyl)phenyl]- ω -hydroxy-	Acute LC50 5.85 mg/L Fresh water	Crustaceans - Ceriodaphnia rigaudi - Neonate	48 hours
3 3 3 1 3 3	Acute LC50 11.2 mg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4500 µg/L Fresh water	Fish - Pimephales promelas	96 hours

Persistence and degradability

There is no data available.





Section 12. Ecological information

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Titanium dioxide	-	352	low
Propane-1,2-diol	-1.07	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT	TDG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

AERG: Not applicable.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.





Section 15. Regulatory information

U.S. Federal regulations

TSCA 8(a) PAIR: Octamethylcyclotetrasiloxane; Poly(oxy-1,2-ethanediyl), α-[4-(1,1,3,3tetramethylbutyl)phenyl]-ω-hydroxy-

TSCA 8(a) CDR Exempt/Partial exemption: Not determined Commerce control list precursor: 2,2',2"-Nitrilotriethanol

United States inventory (TSCA 8b): All components are listed or exempted. Clean Water Act (CWA) 311: Propionic acid; Propylene oxide; Cyclohexane

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

Not listed

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

			SARA 302 TPQ		SARA 302 TPQ SARA 304 RQ		RQ
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)	
Hydrazine Ethylene oxide Propylene oxide	<0.001 <0.1 <0.1	Yes. Yes. Yes.	1000 1000 10000	119.9 - 1444.3	1 10 100	0.12 - 14.4	

SARA 304 RQ : 8037077 lbs / 3648833 kg [796627.8 gal / 3015564.4 L]

SARA 311/312

Classification : Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Titanium dioxide	≥10 - ≤20	No.	No.	No.	No.	Yes.
Propane-1,2-diol	≥5 - ≤5.5	No.	No.	No.	Yes.	No.
Silicon dioxide	≥1 - ≤2	No.	No.	No.	Yes.	No.
Poly(oxy-1,2-ethanediyl), α -[4-(1,1,3,3-tetramethylbutyl)phenyl]- ω -hydroxy-	≥1 - ≤1.5	No.	No.	No.	Yes.	No.

SARA 313

There is no data available.

State regulations

Massachusetts : The following components are listed: Silicon dioxide; Titanium dioxide

New York : None of the components are listed.

New Jersey : The following components are listed: Propane-1,2-diol; Titanium dioxide

Pennsylvania : The following components are listed: Propane-1,2-diol; Silicon dioxide; Titanium dioxide

California Prop. 65





Section 15. Regulatory information

WARNING: This product contains a chemical known to the State of California to cause cancer.

WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	_	Maximum acceptable dosage level
Titanium dioxide	Yes.	No.	No.	No.
Ethanediol	No.	Yes.	No.	No.
Hydrazine	Yes.	No.	Yes.	No.
1,4-Dioxane	Yes.	No.	Yes.	No.
Ethylene oxide	Yes.	Yes.	Yes.	Yes.
Propylene oxide	Yes.	No.	No.	No.

Canada

Canadian lists

Canadian NPRI : The following components are listed: Poly(oxy-1,2-ethanediyl), α -[4-(1,1,3,3-

tetramethylbutyl)phenyl]-ω-hydroxy-

CEPA Toxic substances

: None of the components are listed.

Canada inventory : All components are listed or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification	Justification
CARCINOGENICITY - Category 2	Calculation method
AQUATIC HAZARD (ACUTE) - Category 3	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 3	Calculation method

History

Date of issue mm/dd/yyyy : 08/30/2016

Version : 1

Prepared by : KMK Regulatory Services Inc.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

