



# Glaze Effects

## Product Features

Glaze Effects are translucent water-based colors used to create decorative finishes. For use over stains and paints, Glaze Effects will add depth and character to any piece.

## Recommended Uses

Interior cabinets, trim, doors, and furniture. Use over raw wood, stain, or non-white painted surfaces.

For white surfaces, use GF White Poly or Brushable White Enamel.

## Complies w/ the following air quality regulations:

SCAQMD, CARB, Canada, OTC Phase I & Phase II

**Application Conditions:** Recommended 70°F and 50% humidity, out of direct sunlight. Variations in conditions and application technique can significantly affect dry times and coverage. Use GF Accelerator in cool or humid conditions. Use GF Extender in warm or dry conditions.

**Surface Prep:** Always ensure the surface is clean of contaminants and dust. Sanding any surface too smoothly can reduce adhesion and create application issues like orange peel.

**Raw Wood:** Not recommended.

**Pre-finished Wood:** Clean using 50/50 mix of denatured alcohol and water with maroon non-woven pad. Sand with fine (220-320) foam sanding pad or maroon non-woven pad.

**Other Substrates:** Can be used with proper priming and/or painting. Always test first.

**Application Tips:** For added control, apply 1 coat of any GF topcoat before glazing. When wiping excess glaze, use an absorbent paper towel. If glaze is drying too quickly, dampen wiping cloth with GF Extender. Dry glaze can be removed using a gray non-woven sanding pad.

**System Recommendations:** Seal Glaze Effects with 2-3 coats of GF topcoat to protect color from wearing away.

**Force Dry:** Allow product to flash for 10 minutes at ambient temperature. Using infrared lamps or oven, heat surface to 105°F. Allow to cool before sanding. Allow a minimum of 30 minutes between coats.

**Storage & Shelf Life:** Above 50°F and below 80°F, out of direct sunlight, tightly sealed. Finish preservers such as Bloxygen can help prolong storage life. Best if used within one year of date on can. Unopened and properly stored finish can conservatively last up to 5 years.

**Disposal:** Always dispose of any leftover coatings in accordance with local laws. Do not pour down the drain.

The information and recommendations on this sheet are based upon information gathered at the time of publication and do not act as a safety data sheet. For complete safety and product data, consult the product labels and visit [www.generalfinishes.com](http://www.generalfinishes.com) for complete SDS sheets.

Published April 2019

<b>Product Type:</b>	Water-based glaze
<b>Sheens Available:</b>	N/A
<b>Tintable?:</b>	Yes
<b>Volume Solids:</b>	
<b>Weight Solids:</b>	22%
<b>Rec. Film Thickness:</b>	Wet: 3-5 mils Dry: .75-1.25 mils
<b>Coverage:</b>	Up to 600 sq. ft. per gallon
<b>Viscosity:</b>	Medium
<b>Application:</b>	Brush, roll, or spray
<b>Brush:</b>	Synthetic bristle or foam
<b>Roll:</b>	Short nap or foam
<b>HVLP:</b>	1.1 mm—1.3 mm
<b>Air-Assist Airless:</b>	Not recommended
<b>Airless:</b>	Not recommended
<b>Dry Time (touch):</b>	30 minutes
<b>Dry Time (recoat):</b>	1 hour
<b>Cure Time:</b>	21 days @ 70°F, 50% humidity
<b>Thin With:</b>	Water, GF Extender, GF Accelerator
<b>Clean Hands w/:</b>	Soap & Water
<b>Clean Equipment w/:</b>	GF Brush & Gun Cleaner
<b>Sizes Available:</b>	Pints, Quarts, Gallons
<b>VOC:</b>	Under 304 g/L