



Pro Image Flooring Topcoat

Product Features

Pro Image is a single-component, water-based, topcoat for hardwood floors. It provides exceptional durability for the professional or DIY user with minimal odor and fast dry times. Most importantly, it exceeds MFMA standards for slip resistance.

Recommended Uses

Interior hardwood floors

Complies w/ the following air quality regulations:

SCAQMD, CARB, Canada, OTC Phase I & Phase II

Application Conditions: Recommended 70°F and 50% humidity, out of direct sunlight. Taking surface moisture meter readings is highly recommended before and during application. Variations in conditions and application technique can significantly affect dry times and coverage. Use GF Extender in warm or dry conditions.

Surface Prep: Always ensure the surface is clean of contaminants and dust. Remove dust using a vacuum and water-dampened cloth. Sanding any surface too smoothly can reduce adhesion and create application issues like orange peel.

Raw Wood: Sand with no finer than 220 grit. Ensure any freshly stained surface has dried thoroughly and completely.

Pre-finished Wood: Clean using commercial floor cleaner to remove any built up waxes and residue. Sand with maroon non-woven pad. Always test for adhesion and performance in a small, hidden area.

Other Substrates: Not recommended

Sanding Between Coats: If recoating within 24 hours, sanding is not required unless a smoother surface is desired. When needed, use fine (240) sandpaper or maroon non-woven pad.

System Recommendations: 3-4 total coats of finish are recommended on raw wood.

Traffic: Floors may be carefully walked on (socks only) after 6 hours. Furniture can be replaced (with protective pads) after 3 days. Rugs can be replaced and normal use is safe after 10 days.

Storage & Shelf Life: Above 50°F and below 80°F, out of direct sunlight, tightly sealed. Finish preservers such as Bloxygen can help prolong storage life. Best if used within one year of date on can. Unopened and properly stored finish can conservatively last up to 5 years.

Disposal: Always dispose of any leftover coatings in accordance with local laws. Do not pour down the drain.

The information and recommendations on this sheet are based upon information gathered at the time of publication and do not act as a safety data sheet. For complete safety and product data, consult the product labels and visit www.generalfinishes.com for complete SDS sheets.

Published March 2020

Product Type:	Water-based acrylic/urethane blend
Sheens Available:	Satin (30), Semi-Gloss (55)
Tintable?:	No
Volume Solids:	29%
Weight Solids:	32%
Rec. Film Thickness:	Wet: 3-5 mils Total Dry (multiple coats): 2.5-5 mils
Coverage:	450 sq. ft. per gallon
Viscosity:	Thin (150-300 cPs)
Application:	Recommended using T-bar applicator
Brush:	Pad applicator can be used
Roll:	Microfiber
HVLP:	Not recommended
Air-Assist Airless:	Not recommended
Airless:	Not recommended
Dry Time (touch):	45 minutes
Dry Time (recoat):	2-4 hours
Cure Time:	10 days @ 70°F, 50% humidity
Thin With:	GF Extender
Clean Hands w/:	Soap & Water
Clean Equipment w/:	GF Brush & Gun Cleaner
Sizes Available:	Gallons
VOC:	Under 224 g/L