



Seal-A-Cell

Product Features

Oil-based Seal-A-Cell is a unique combination of oils and waxes that penetrates deep into wood, highlighting its natural beauty with a “close to the wood” finish. This finish ambers over time while providing water and chemical resistance. It can also be used as a pre-stain conditioner.

Recommended Uses

Interior raw wood surfaces such as cabinets, trim, doors, and furniture.

Complies w/ the following air quality regulations:
Canada. Check local regulations for United States

Application Conditions: Recommended 70°F and 50% humidity, out of direct sunlight, with good air movement. Variations in conditions and application technique can significantly affect dry times and coverage.

Surface Prep: Always ensure the surface is clean of contaminants and dust. Sanding any surface too smoothly can reduce adhesion and create application issues

Raw Wood: Sand progressively finer up 220 grit. Sanding finer than 220 grit is not recommended

Pre-finished Wood: Not recommended

Other Substrates: Not recommended.

Application Tips: Apply using a rag, brush or paint pad applicator. Make sure to wipe off excess with a clean cloth.

System Recommendations: 1-2 coats of Seal-A-Cell are recommended. For added protection, follow with 2-3 coats of Arm-R-Seal.

Storage & Shelf Life: Above 50°F and below 80°F, out of direct sunlight, tightly sealed. Minimize oxygen exposure to prevent drying in the can. Finish preservers such as Bloxygen can help. Best if used within one year of purchase. Unopened and properly stored finish can conservatively last up to 5 years.

Disposal: Always dispose of any leftover coatings in accordance with local laws. Do not pour down the drain. Dispose of any rags and brushes in a fireproof container to prevent spontaneous combustion.

The information and recommendations on this sheet are based upon information gathered at the time of publication and do not act as a safety data sheet. For complete safety and product data, consult the product labels and visit www.generalfinishes.com for complete SDS sheets.

Published March 2020

Product Type:	Penetrating oil & urethane sealer
Sheens Available:	Gloss (80+)
Tintable?:	Yes
Volume Solids:	27%
Weight Solids:	33%
Rec. Film Thickness:	N/A
Coverage:	Up to 600 sq. ft. per gallon
Viscosity:	Thin
Application:	Wipe or brush
Brush:	Natural bristle or foam
Roll:	Short nap or foam
HVLP:	N/A
Air-Assist Airless:	N/A
Airless:	N/A
Dry Time (touch):	12+ hours
Dry Time (recoat):	24+ hours
Cure Time:	30 days
Thin With:	Not recommended
Clean Hands w/:	Mineral spirits, waterless hand cleaner
Clean Equipment w/:	Mineral spirits
Sizes Available:	Pints, Quarts, Gallons Local availability varies by VOC regulations
VOC:	565 g/L