



# General Finishes Enduro Water-Based Topcoat

## Product Comparison Chart



Scan QR code to compare GF products.

Enduro Water Based Sanding Sealer	Enduro Pre-Cat Lacquer	Enduro Clear Poly	Enduro Conversion Varnish	Enduro-Var Water Based Urethane Topcoat	Exterior 450 Topcoat
					
Faster Building, Easier Sanding, Economical Price	Production Shops, Fast Stack Times, Economical Price	Spray-Only, Durable Clear	Catalyzed, Most Durable Interior/Exterior Clear	Ambering Water-Based	Exterior Clear
<b>Suggested Use</b>	<b>Suggested Use</b>	<b>Suggested Use</b>	<b>Suggested Use</b>	<b>Suggested Use</b>	<b>Suggested Use</b>
Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork	Commercial Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork	Exterior Furniture, Doors
<b>Ambering</b>	<b>Ambering</b>	<b>Ambering</b>	<b>Ambering</b>	<b>Ambering</b>	<b>Ambering</b>
No	No	No	No	Yes	No
<b>Sheen</b>	<b>Sheen</b>	<b>Sheen</b>	<b>Sheen</b>	<b>Sheen</b>	<b>Sheen</b>
NA.	Flat, Satin, Semi-Gloss, Gloss	Flat, Satin, Semi-Gloss, Gloss	Flat, Satin, Semi-Gloss, Gloss	Flat, Satin, Semi-Gloss, Gloss	Flat, Satin, Semi-Gloss, Gloss
<b>Interior or Exterior</b>	<b>Interior or Exterior</b>	<b>Interior or Exterior</b>	<b>Interior or Exterior</b>	<b>Interior or Exterior</b>	<b>Interior or Exterior</b>
Interior Only	Interior Only	Interior Only	Interior/Exterior - No Decks	Interior Only	Exterior - No Decks
<b>Type</b>	<b>Type</b>	<b>Type</b>	<b>Type</b>	<b>Type</b>	<b>Type</b>
Acrylic	Self-Crosslinking Acrylic	Urethane/Acrylic Blend	Urethane/Acrylic Blend	Oil-Modified Urethane	Urethane/Acrylic Blend
<b>Can sizes</b>	<b>Can sizes</b>	<b>Can sizes</b>	<b>Can sizes</b>	<b>Can sizes</b>	<b>Can sizes</b>
Quarts, Gallons, 5 Gallon*	Gallons, 5 Gallon*	Gallons, 5 Gallon*	Gallons, 5 Gallon*	Quarts, Gallon, 5 Gallon	Quarts, Gallons, 5 Gallon*
<b>Coverage</b>	<b>Coverage</b>	<b>Coverage</b>	<b>Coverage</b>	<b>Coverage</b>	<b>Coverage</b>
600 Sq. Ft./Gal.	600 Sq. Ft./Gal.	450 Sq. Ft./Gal.	450 Sq. Ft./Gal.	500-600 Sq. Ft./Gal.	560-640 Sq. Ft./Gal.
<b>Coats</b>	<b>Coats</b>	<b>Coats</b>	<b>Coats</b>	<b>Coats</b>	<b>Coats</b>
1-2 Coats	3 Coats	3 Coats	3 Coats	3 Coats	2-3 Coats
<b>Application</b>	<b>Application</b>	<b>Application</b>	<b>Application</b>	<b>Application</b>	<b>Application</b>
Spray	Spray	Spray	Spray	Brush, Roll, Spray	Brush, Roll, Spray
<b>Over existing finishes</b>	<b>Over existing finishes</b>	<b>Over existing finishes</b>	<b>Over existing finishes</b>	<b>Over existing finishes</b>	<b>Over existing finishes</b>
Yes	Yes	Yes	Yes	No	Yes
<b>Tip Size</b>	<b>Tip Size</b>	<b>Tip Size</b>	<b>Tip Size</b>	<b>Tip Size</b>	<b>Tip Size</b>
HVLP 1.1mm-1.3mm	HVLP 1.1mm-1.3mm	HVLP 1.1mm-1.3mm	HVLP 1.1mm-1.3mm	HVLP 1.1mm-1.3mm	HVLP 1.1mm-1.3mm
<b>Dry time-touch</b>	<b>Dry time-touch</b>	<b>Dry time-touch</b>	<b>Dry time-touch</b>	<b>Dry time-touch</b>	<b>Dry time-touch</b>
30 Min.	10 Min.	30 Min.	30 Min.	30 Min.	30+ Min.
<b>Dry time-recoat</b>	<b>Dry time-recoat</b>	<b>Dry time-recoat</b>	<b>Dry time-recoat</b>	<b>Dry time-recoat</b>	<b>Dry time-recoat</b>
2 Hr.	1 Hr.	2 Hr.	2 Hr.	4 Hr.	2+ Hr.
<b>Dry time-light use</b>	<b>Dry time-light use</b>	<b>Dry time-light use</b>	<b>Dry time-light use</b>	<b>Dry time-light use</b>	<b>Dry time-light use</b>
7-10 Days	7-10 Days	7-10 Days	72 Hr.	7-10 Days	7-10 Days
<b>Stack times — 70°F, 50% RH</b>	<b>Stack times — 70°F, 50% RH</b>	<b>Stack times — 70°F, 50% RH</b>	<b>Stack times — 70°F, 50% RH</b>	<b>Stack times — 70°F, 50% RH</b>	<b>Stack times — 70°F, 50% RH</b>
12+ Hours Dependent On Conditions	12+ Hours Dependent On Conditions	12+ Hours Dependent On Conditions	12+ Hours Dependent On Conditions	12+ Hours Dependent On Conditions	12+ Hours Dependent On Conditions
<b>Dry time-cure</b>	<b>Dry time-cure</b>	<b>Dry time-cure</b>	<b>Dry time-cure</b>	<b>Dry time-cure</b>	<b>Dry time-cure</b>
21 Days	21 Days	21 Days	7 Days	21 Days	21 Days
<b>Durability</b>	<b>Durability</b>	<b>Durability</b>	<b>Durability</b>	<b>Durability</b>	<b>Durability</b>
Medium	Medium	High	Highest	Medium	High
<b>Water Resistance</b>	<b>Water Resistance</b>	<b>Water Resistance</b>	<b>Water Resistance</b>	<b>Water Resistance</b>	<b>Water Resistance</b>
3	5	5	5	3	5
<b>Chemical Resistance</b>	<b>Chemical Resistance</b>	<b>Chemical Resistance</b>	<b>Chemical Resistance</b>	<b>Chemical Resistance</b>	<b>Chemical Resistance</b>
91	89	98	101	84	92
<b>Viscosity</b>	<b>Viscosity</b>	<b>Viscosity</b>	<b>Viscosity</b>	<b>Viscosity</b>	<b>Viscosity</b>
Medium	Medium	Medium	Medium	Thin	Medium
<b>Weight Solids</b>	<b>Weight Solids</b>	<b>Weight Solids</b>	<b>Weight Solids</b>	<b>Weight Solids</b>	<b>Weight Solids</b>
30%	28%	28%	28%	28%	31%
<b>Volume Solids</b>	<b>Volume Solids</b>	<b>Volume Solids</b>	<b>Volume Solids</b>	<b>Volume Solids</b>	<b>Volume Solids</b>
25%	23%	31%	27%	23%	32%
<b>VOC</b>	<b>VOC</b>	<b>VOC</b>	<b>VOC</b>	<b>VOC</b>	<b>VOC</b>
<122 g/L	<270.937 g/L	<233 g/L	<197 g/L	<250 g/L	<123.009 g/L

GENERAL FINISHES • 2462 Corporate Circle, East Troy, Wisconsin • [www.GeneralFinishes.com](http://www.GeneralFinishes.com)



Tomorrow's Wood Finishes Today  
Made in the USA

\*55 gallon drums are available upon request.