# **SAFETY DATA SHEET**

Waterbased wood stain Graphite



### Section 1. Identification

**Product type** 

- : Waterbased wood stain Graphite
- : BLK335
- : Not available.
  - : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

### Identified uses Wood stain.

Supplier's details	: General Finishes 2462 Corporate Circle East Troy, WI 53120 U.S.A. Phone no.: 262-642-4545 Toll free no.: 1-800-783-6050 Fax no.: 262-642-4707 Web: GeneralFinishes.com	Supplier's details for Canada
Emergency telephone number (with hours of operation)	: CHEMTREC, U.S.: 1-800-424-9300 (24/7)	International: +1-703-527-3887

# Section 2. Hazard(s) identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 1
GHS label elements	
Hazard pictograms	
Signal word	
Signal word	: Danger
Hazard statements	: H350 - May cause cancer.
Precautionary statement	<u>s</u>
Prevention	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> </ul>
	P280 - Wear protective gloves, protective clothing and eye or face protection.



### Section 2. Hazard(s) identification

Storage

: P405 - Store locked up.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified (US)

## Section 3. Composition/information on ingredients

Substance/mixture		
Other means of		
identification		

: Mixture

: Not available.

: None known.

Ingredient name	% (w/w)	CAS number
Titanium dioxide	3 - 7	13463-67-7
Propane-1,2-diol	1 - 5	57-55-6
Carbon black, non respirable	0.5 - 1.5	1333-86-4
Talc	0.1 - 1	14807-96-6
1,2-Benzisothiazol-3(2H)-one	<0.1	2634-33-5

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necess	ary first aid measures
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed





### Section 4. First aid measures

Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/symp</u>	<u>otoms</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: In case of fire, use water spray (fog), foam, dry chemical or CO <sub>2</sub> .
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: No specific fire or explosion hazard.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.





### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Spill	÷	Stop leak if without risk. Move containers from spill area. Approach release from

Spill	Stop leak if without risk. Move containers from spill area. Approach release from
	upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash
	spillages into an effluent treatment plant or proceed as follows. Contain and collect
	spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or
	diatomaceous earth and place in container for disposal according to local regulations
	(see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated
	absorbent material may pose the same hazard as the spilled product. Note: see
	Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

### **Precautions for safe handling**

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store between the following temperatures: 0 to 37.778°C (32 to 100°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.





### Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **United States**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Titanium dioxide	ACGIH TLV (United States, 3/2020). TWA: 10 mg/m <sup>3</sup> 8 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
Propane-1,2-diol	AIHA WEEL (United States, 7/2020).
	TWA: 10 mg/m³ 8 hours.
Carbon black, non respirable	ACGIH TLV (United States, 3/2020).
	TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable
	fraction
	NIOSH REL (United States, 10/2016).
	TWA: 3.5 mg/m <sup>3</sup> 10 hours. TWA: 0.1 mg of PAHs/cm <sup>3</sup> 10 hours.
	OSHA PEL (United States, 5/2018).
	TWA: 3.5 mg/m <sup>3</sup> 8 hours.
Talc	ACGIH TLV (United States, 3/2020).
	TWA: 0.1 f/cc 8 hours. Form: Respirable
	fibers: length greater than 5 uM; aspect ratio
	equal to or greater than 3:1 as determined by
	the membrane filter method at 400-450X
	magnification (4-mm objective) phase contrast illumination.
	OSHA PEL Z3 (United States, 6/2016).
	TWA: 0.1 f/cc 8 hours. Form: containing
	asbestos
	STEL: 1 f/cc 30 minutes. Form: containing
	asbestos
1,2-Benzisothiazol-3(2H)-one	None.

#### <u>Canada</u>

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Titanium dioxide	CA British Columbia Provincial (Canada, 1/2020). TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Total dust CA Quebec Provincial (Canada, 7/2019). TWAEV: 10 mg/m <sup>3</sup> 8 hours. Form: Total dust CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m <sup>3</sup> 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m <sup>3</sup> 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m <sup>3</sup> 15 minutes. TWA: 10 mg/m <sup>3</sup> 8 hours.
Propane-1,2-diol	<b>CA Ontario Provincial (Canada, 6/2019).</b> TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Aerosol only

Tel:+1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



# Section 8. Exposure controls/personal protection

Carbon black, non respirablefraction TWA: 50 ppm 8 hours. Form: Vapor fractic CA British Columbia Provincial (Canada, 1/2020). TWA: 3 mg/m³ 8 hours. Form: Inhalable CA Ontario Provincial (Canada, 6/2019). TWA: 3 mg/m³ 8 hours. Form: Inhalable particulate matter. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWAEV: 3 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). TWAEV: 3 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.1 f/cc 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		
Carbon black, non respirableTWA: 50 ppm 8 hours. Form: Vapor fractionCarbon black, non respirableCA British Columbia Provincial (Canada, 1/2020). TWA: 3 mg/m³ 8 hours. Form: Inhalable CA Ontario Provincial (Canada, 6/2019). TWA: 3 mg/m³ 8 hours. Form: Inhalable particulate matter.CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours.8 hrs OEL: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours.TWA: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours.TWA: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours.TWA: 3.5 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust. CA British Columbia Provincial (Canada, 1/2020). TWAEV: 3 mg/m³ 8 hours.TalcCA Saskatchewan Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust. CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		TWA: 155 mg/m <sup>3</sup> 8 hours. Form: Vapor
Carbon black, non respirableCA British Columbia Provincial (Canada, 1/2020). TWA: 3 mg/m³ 8 hours. Form: Inhalable CA Ontario Provincial (Canada, 6/2019). TWA: 3 mg/m³ 8 hours. Form: Inhalable particulate matter. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours. CA Gauebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours. CA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.1 f/cc 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		
1/2020).TWA: 3 mg/m³ 8 hours. Form: InhalableCA Ontario Provincial (Canada, 6/2019).TWA: 3 mg/m³ 8 hours. Form: Inhalableparticulate matter.CA Alberta Provincial (Canada, 6/2018).8 hrs OEL: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019).TWAEV: 3.5 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2013).STEL: 7 mg/m³ 15 minutes.TWA: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019).TWAEV: 3 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019).TWAEV: 3 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019).TWAEV: 3 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2019).TWAEV: 3 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2019).TWAEV: 3 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2013).TWA: 0.1 f/cc 8 hours.CA Saskatchewan Provincial (Canada, 7/2013).TWA: 2 mg/m³ 8 hours.TWA: 2 mg/m³ 8 hours.		
TWA: 3 mg/m³ 8 hours. Form: InhalableCA Ontario Provincial (Canada, 6/2019).TWA: 3 mg/m³ 8 hours. Form: Inhalableparticulate matter.CA Alberta Provincial (Canada, 6/2018).8 hrs OEL: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019).TWAEV: 3.5 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2019).TWAEV: 3.5 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2013).STEL: 7 mg/m³ 15 minutes.TWA: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019).TWA: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019).TWA: 3 mg/m³ 8 hours. Form: Respiral dust.CA British Columbia Provincial (Canada, 1/2020).TWA: 0.1 f/cc 8 hours.CA Saskatchewan Provincial (Canada, 7/2013).TWA: 0.1 mg/m³ 8 hours. Form: respirable	Carbon black, non respirable	• •
CA Ontario Provincial (Canada, 6/2019). TWA: 3 mg/m³ 8 hours. Form: Inhalable particulate matter.CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours.TalcCA Saskatchewan Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust. CA Saskatchewan Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours. CA Saskatchewan Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours. Form: respirable		1/2020).
<ul> <li>TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable particulate matter.</li> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m<sup>3</sup> 8 hours.</li> <li>CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m<sup>3</sup> 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m<sup>3</sup> 15 minutes. TWA: 3.5 mg/m<sup>3</sup> 8 hours.</li> <li>Talc</li> <li>CA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m<sup>3</sup> 8 hours. Form: Respiral dust.</li> <li>CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.1 f/cc 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: respirable</li> </ul>		
particulate matter.CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours.S hrs OEL: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.TalcTalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust. CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours.CA Saskatchewan Provincial (Canada, 1/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		CA Ontario Provincial (Canada, 6/2019).
CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust. CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours.TAIC		TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable
8 hrs OEL: 3.5 mg/m³ 8 hours.CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust.CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		
CA Quebec Provincial (Canada, 7/2019). TWAEV: 3.5 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust.CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		
TWAEV: 3.5 mg/m³ 8 hours.CA Saskatchewan Provincial (Canada, 7/2013).STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust.CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		
CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust. CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		
7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust.CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		
TalcSTEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours.TalcCA Quebec Provincial (Canada, 7/2019). TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust.CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours.CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable		CA Saskatchewan Provincial (Canada,
Talc       TWA: 3.5 mg/m³ 8 hours.         CA Quebec Provincial (Canada, 7/2019).       TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust.         CA British Columbia Provincial (Canada, 1/2020).       TWA: 0.1 f/cc 8 hours.         CA Saskatchewan Provincial (Canada, 7/2013).       TWA: 2 mg/m³ 8 hours. Form: respirable		,
Talc       CA Quebec Provincial (Canada, 7/2019).         TWAEV: 3 mg/m³ 8 hours. Form: Respiral dust.         CA British Columbia Provincial (Canada, 1/2020).         TWA: 0.1 f/cc 8 hours.         CA Saskatchewan Provincial (Canada, 7/2013).         TWA: 2 mg/m³ 8 hours. Form: respirable		
TWAEV: 3 mg/m <sup>3</sup> 8 hours. Form: Respiral dust. <b>CA British Columbia Provincial (Canada,</b> <b>1/2020).</b> TWA: 0.1 f/cc 8 hours. <b>CA Saskatchewan Provincial (Canada,</b> <b>7/2013).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: respirable		TWA: 3.5 mg/m³ 8 hours.
dust. <b>CA British Columbia Provincial (Canada,</b> <b>1/2020).</b> TWA: 0.1 f/cc 8 hours. <b>CA Saskatchewan Provincial (Canada,</b> <b>7/2013).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: respirable	Talc	CA Quebec Provincial (Canada, 7/2019).
CA British Columbia Provincial (Canada, 1/2020). TWA: 0.1 f/cc 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m <sup>3</sup> 8 hours. Form: respirable		TWAEV: 3 mg/m <sup>3</sup> 8 hours. Form: Respirable
<b>1/2020).</b> TWA: 0.1 f/cc 8 hours. <b>CA Saskatchewan Provincial (Canada,</b> <b>7/2013).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: respirable		
TWA: 0.1 f/cc 8 hours. <b>CA Saskatchewan Provincial (Canada,</b> <b>7/2013).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: respirable		• •
<b>CA Saskatchewan Provincial (Canada,</b> <b>7/2013).</b> TWA: 2 mg/m <sup>3</sup> 8 hours. Form: respirable		1/2020).
<b>7/2013).</b> TWA: 2 mg/m³ 8 hours. Form: respirable		
TWA: 2 mg/m <sup>3</sup> 8 hours. Form: respirable		•
•		
Ifraction		•
Inaction		fraction

Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
Individual protection measur	<u>res</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.



### Section 8. Exposure controls/personal protection

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid. [Viscous.]
Color	: Gray.
Odor	: Slight.
Odor threshold	: Not available.
рН	: 7.5 to 9
Melting/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flash point	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.06
Solubility	: Soluble in water.
Solubility in water	: Soluble.
Partition coefficient: n- octanol/water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Dynamic: 150 to 350 mPa⋅s (150 to 350 cP)
VOC content	: <135 g/L
Flow time (ISO 2431)	: Not available.

### Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	The product is stable.
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.



Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



### Section 10. Stability and reactivity

Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials.
Conditions to avoid	: Protect from freezing.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
Carbon black, non respirable	LD50 Oral	Rat	>15400 mg/kg	-
1,2-Benzisothiazol-3(2H)-one	LD50 Oral	Rat	1020 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Talc	Skin - Mild irritant	Human	-	72 hours 300	-
				µg Intermittent	
1,2-Benzisothiazol-3(2H)-one	Skin - Mild irritant	Human	-	48 hours 5 %	-

#### **Sensitization**

There is no data available.

#### **Mutagenicity**

There is no data available.

#### **Carcinogenicity**

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Titanium dioxide Talc	-	2B 1	-

#### **Reproductive toxicity**

There is no data available.

#### **Teratogenicity**

There is no data available.

#### Specific target organ toxicity (single exposure)

There is no data available.

#### Specific target organ toxicity (repeated exposure)

There is no data available.

#### Aspiration hazard

There is no data available.





Information on the likely

#### Waterbased wood stain Graphite

### Section 11. Toxicological information

routes of exposure	· Noties of entry anticipated. Oral, Dennal.
Potential acute health effect	<u>S</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	vsical, chemical and toxicological characteristics
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Delayed and immediate effe	<u>cts and also chronic effects from short and long term exposure</u>
<u>Short term exposure</u>	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
<u>Long term exposure</u>	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Potential chronic health eff	ects
General	: No known significant effects or critical hazards.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

: Routes of entry anticipated: Oral, Dermal.

#### Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name			(gases)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
Propane-1,2-diol	20000	20800	N/A	N/A	N/A
1,2-Benzisothiazol-3(2H)-one	1020	N/A	N/A	N/A	N/A



### Section 12. Ecological information

#### <u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
Titanium dioxide	Acute LC50 >1000000 µg/L Marine water	Fish - Fundulus heteroclitus	96 hours
Propane-1,2-diol	Acute EC50 >110 ppm Fresh water	Daphnia - Daphnia magna	48 hours
•	Acute LC50 1020000 µg/L Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 710000 µg/L Fresh water	Fish - Pimephales promelas	96 hours
Carbon black, non respirable	Acute EC50 37.563 mg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
1,2-Benzisothiazol-3(2H)-one	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/L Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours

#### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Propane-1,2-diol	-1.07	-	low

#### Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

#### Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.





### Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.

**AERG** : Not applicable

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

### Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) CDR Exempt/Partial exemption: Not determined
	Commerce control list precursor: Triethanolamine
	<b>Clean Water Act (CWA) 311</b> : Sodium hydroxide; Cyclohexane; Phosphoric acid; Formaldehyde

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed

#### SARA 302/304

**Composition/information on ingredients** 

			SARA 302 TPQ SARA 304 RQ		RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ethylene oxide Formaldehyde	≤0.00001 ≤0.00001	Yes. Yes.	1000 500	- 73.9	10 100	- 14.8



### Section 15. Regulatory information

**SARA 304 RQ** 

: 3632821299 lbs / 1649300869.7 kg [411036976.5 gal / 1555944216.7 L]

SARA 311/312 Classification

#### : CARCINOGENICITY - Category 1A

#### Composition/information on ingredients

Name	%	Classification
Titanium dioxide Talc		CARCINOGENICITY - Category 2 CARCINOGENICITY - Category 1A

#### **State regulations**

Massachusetts	: The following components are listed: Titanium dioxide; Carbon black, non respirable
New York	: None of the components are listed.
New Jersey	<ul> <li>The following components are listed: Titanium dioxide; Propane-1,2-diol; Carbon black, non respirable; Talc</li> </ul>
Pennsylvania	<ul> <li>The following components are listed: Titanium dioxide; Propane-1,2-diol; Carbon black, non respirable</li> </ul>

#### California Prop. 65

▲ WARNING: This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Titanium dioxide, Carbon black, non respirable, Talc, Crystalline silica, respirable powder, Ethyl acrylate, Diethanolamine, 1,4-Dioxane and Formaldehyde, which are known to the State of California to cause cancer, and Ethanediol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Titanium dioxide	-	-
Carbon black, non respirable	-	-
Talc	-	-
Crystalline silica, respirable powder	-	-
Ethyl acrylate	-	-
Ethanediol	-	Yes.
Diethanolamine	-	-
1,4-Dioxane	Yes.	-
Ethylene oxide	Yes.	Yes.
Formaldehyde	Yes.	-

**Canadian lists** 

- Canadian NPRI
- : None of the components are listed.
- : None of the components are listed.

#### CEPA Toxic substances International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Ingredient name	List name	Status
Triethanolamine	Schedule III	Listed

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.



### Section 15. Regulatory information

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory list**

Canada : Not determined. **United States (TSCA 8b)** 

: Not determined.

### Section 16. Other information

#### Procedure used to derive the classification

Classification	Justification
CARCINOGENICITY - Category 1	Calculation method

<u>History</u>	
Date of issue/Date of revision	: 08/15/2021
Date of previous issue	: Not applicable
Version	: 1
Prepared by	: KMK Regulatory Services Inc.
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.