# SAFETY DATA SHEET

## **Exterior 450 Coffee Bean Stain**



Section 1. Identification		
GHS product identifier	: Exterior 450 Coffee Bean Stain	
Product code	: Not available.	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses o	f the substance or mixture and uses advised against	
Identified uses	: Water-based stain.	
Manufacturer	: General Finishes 2462 Corporate Circle East Troy, WI 53120 U.S.A. Phone no.: 262-642-4545 Toll free no.: 1-800-783-6050 Fax no.: 262-642-4707 Web: GeneralFinishes.com	
Emergency telephone number (with hours of operation)	: CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3887 (24/7)	

# Section 2. Hazards identification

OSHA/HCS status	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).	
Classification of the substance or mixture	: CARCINOGENICITY - Category 2 AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1	
GHS label elements		
Hazard pictograms		
Signal word	: Warning	
Hazard statements	<ul> <li>H351 - Suspected of causing cancer.</li> <li>H410 - Very toxic to aquatic life with long lasting effects.</li> </ul>	
Precautionary statements		
Prevention	<ul> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.</li> <li>P273 - Avoid release to the environment.</li> </ul>	
Response	<ul> <li>P391 - Collect spillage.</li> <li>P308 + P313 - IF exposed or concerned: Get medical attention.</li> </ul>	
Storage	: P405 - Store locked up.	
KMK Regulatory Services	Tel: +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767)         1/12           www.kmkregservices.com         www.askdrluc.com         www.ghssmart.com         1/12	



## Section 2. Hazards identification

**Disposal** 

- : P501 Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazards not otherwise classified

## Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

: None known.

Other means of identification

: Not available.

Ingredient name	%	CAS number
Diiron trioxide	1 - 5	1309-37-1
Carbon black, respirable powder	0.1 - 1	1333-86-4
Amines, tallow alkyl, ethoxylated	0.001 - 0.1	61791-26-2
Carbendazim	0.001 - 0.1	10605-21-7
3-lodo-2-propynyl butylcarbamate	0.001 - 0.1	55406-53-6
N'-tert-butyl-N-cyclopropyl-6-(methylthio)-1,3,5-triazine-2,4-diamine	0.001 - 0.1	28159-98-0
Chromium	0.001 - 0.1	7440-47-3

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

Description of necessary first	aid measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact	: No known significant effects or critical hazards.	
KMK Regulatory Services	Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com	2/12



# Section 4. First aid measures

Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Over-exposure signs/symp	u <u>toms</u>		
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Indication of immediate med	lical attention and special treatment needed, if necessary		
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.		
Specific treatments	: No specific treatment.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.		

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: In case of fire, use water spray (fog), foam, dry chemical or CO <sub>2</sub> .
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	



## Section 6. Accidental release measures

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

Spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in original container pro direct sunlight in a dry, cool and well-ventilated area, away from incompati (see Section 10) and food and drink. Store locked up. Keep container tig and sealed until ready for use. Containers that have been opened must be resealed and kept upright to prevent leakage. Do not store in unlabeled of Use appropriate containment to avoid environmental contamination. See incompatible materials before handling or use.	

## Section 8. Exposure controls/personal protection

## Control parameters

United States Occupational exposure limits

Ingredient name	Exposure limits
Diiron trioxide Carbon black, respirable powder	NIOSH REL (United States, 10/2016).TWA: 5 mg/m³, (as Fe) 10 hours. Form: Dust and fumesOSHA PEL (United States, 5/2018).TWA: 10 mg/m³ 8 hours.ACGIH TLV (United States, 3/2018).TWA: 5 mg/m³ 8 hours. Form: Respirable fractionNIOSH REL (United States, 10/2016).TWA: 3.5 mg/m³ 10 hours.TWA: 0.1 mg of PAHs/cm³ 10 hours.OSHA PEL (United States, 5/2018).TWA: 3.5 mg/m³ 8 hours.ACGIH TLV (United States, 5/2018).TWA: 0.1 mg of PAHs/cm³ 10 hours.OSHA PEL (United States, 5/2018).TWA: 3.5 mg/m³ 8 hours.ACGIH TLV (United States, 3/2018).



Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



# Section 8. Exposure controls/personal protection

	TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction
Amines, tallow alkyl, ethoxylated	None.
Carbendazim	None.
3-lodo-2-propynyl butylcarbamate	None.
N'-tert-butyl-N-cyclopropyl-6-(methylthio)-1,3,5-triazine-2,4-diamine	None.
Chromium	NIOSH REL (United States, 10/2016).
	TWA: 0.5 mg/m <sup>3</sup> 8 hours.
	ACGIH TLV (United States, 3/2018).
	TWA: 0.5 mg/m <sup>3</sup> , (measured as Cr) 8 hours. Form: Inhalable fraction
	OSHA PEL (United States, 5/2018).
	TWA: 1 mg/m³, (as Cr) 8 hours.

#### **Canada**

#### **Occupational exposure limits**

Ingredient name	Exposure limits
Diiron trioxide	<ul> <li>CA British Columbia Provincial (Canada, 7/2018). TWA: 5 mg/m³, (as Fe) 8 hours. Form: Dust TWA: 5 mg/m³, (as Fe) 8 hours. Form: Fertilizer and/or industrial use. STEL: 10 mg/m³, (as Fe) 15 minutes. Form: Fertilizer and/or industrial use. TWA: 3 mg/m³ 8 hours. Form: Respirable dust TWA: 10 mg/m³ 8 hours. Form: Total dust CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 5 mg/m³ 8 hours. Form: Respirable CA Ontario Provincial (Canada, 1/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction CA Quebec Provincial (Canada, 1/2014). TWAEV: 5 mg/m³, (as Fe) 8 hours. Form: dust and fume CA Saskatchewan Provincial (Canada, 7/2013). STEL: 10 mg/m³, (measured as Fe) 15 minutes. Form: dust and fume TWA: 5 mg/m³, (measured as Fe) 8 hours. Form: dust and fume</li> </ul>
Carbon black, respirable powder	CA British Columbia Provincial (Canada, 7/2018). TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m <sup>3</sup> 8 hours. CA Quebec Provincial (Canada, 1/2014). TWAEV: 3.5 mg/m <sup>3</sup> 8 hours. CA Ontario Provincial (Canada, 1/2018). TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m <sup>3</sup> 15 minutes. TWA: 3.5 mg/m <sup>3</sup> 8 hours.
Chromium	<ul> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>8 hrs OEL: 0.5 mg/m<sup>3</sup>, (as Cr) 8 hours.</li> <li>CA Ontario Provincial (Canada, 1/2018).</li> <li>TWA: 0.5 mg/m<sup>3</sup>, (as Cr) 8 hours. Form: Inorganic</li> <li>CA British Columbia Provincial (Canada, 7/2018).</li> <li>TWA: 0.5 mg/m<sup>3</sup> 8 hours.</li> <li>CA Quebec Provincial (Canada, 1/2014).</li> <li>TWAEV: 0.5 mg/m<sup>3</sup> 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 1.5 mg/m<sup>3</sup>, (measured as Cr) 8 hours.</li> <li>TWA: 0.5 mg/m<sup>3</sup>, (measured as Cr) 8 hours.</li> </ul>

Appropriate engineering controls	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

#### **Individual protection measures**



## Section 8. Exposure controls/personal protection

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid. [Viscous.]
Color	: Brown.
Odor	: Slight
Odor threshold	: Not available.
рН	: 8.9
Melting point	: Not available.
Boiling point	: >100°C (>212°F)
Flash point	: Closed cup: >98.889°C (>210°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.05
Solubility	: Soluble in water.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.



Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



## Section 9. Physical and chemical properties

Decomposition temperature	: Not available.
Viscosity	: Dynamic (room temperature): 500 mPa·s (500 cP)
VOC content	: 74.473 g/L
Flow time (ISO 2431)	: Not available.

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Protect from freezing.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Carbon black, respirable powder	LD50 Oral	Rat	>15400 mg/kg	-
Amines, tallow alkyl, ethoxylated	LD50 Dermal	Rat	>10 g/kg	-
	LD50 Oral	Rat	500 mg/kg	-
Carbendazim	LD50 Dermal	Rabbit	8500 mg/kg	-
	LD50 Dermal	Rat	2 g/kg	-
	LD50 Oral	Rat	>5050 mg/kg	-
3-lodo-2-propynyl butylcarbamate	LD50 Oral	Rat	1470 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Amines, tallow alkyl, ethoxylated	5	Rabbit Rabbit	-	100 mg 24 hours 100 µl	-

#### Sensitization

There is no data available.

#### **Mutagenicity**

There is no data available.

### **Carcinogenicity**

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Diiron trioxide	-	3	-
Carbon black, respirable powder	-	2B	-
Chromium	-	3	-

#### Reproductive toxicity

There is no data available.

#### Teratogenicity



## Section 11. Toxicological information

#### There is no data available.

#### Specific target organ toxicity (single exposure)

#### There is no data available.

#### Specific target organ toxicity (repeated exposure)

Name	Category	Target organs
3-lodo-2-propynyl butylcarbamate	Category 1	larynx

#### **Aspiration hazard**

There is no data available.

Information on the likely routes of exposure	:	Dermal contact. Eye contact. Ingestion.
Potential acute health effects		
Eye contact	1	No known significant effects or critical hazards.

# Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure		
Potential immediate effects	known significant effects or critica	al hazards.
Potential delayed effects	known significant effects or critica	al hazards.
<u>Long term exposure</u>		
Potential immediate effects	known significant effects or critica	al hazards.
Potential delayed effects	known significant effects or critica	al hazards.
Potential chronic health eff		
General	known significant effects or critica	al hazards.
Carcinogenicity	pected of causing cancer. Risk o osure.	of cancer depends on duration and level of
Mutagenicity	known significant effects or critica	al hazards.
Teratogenicity	known significant effects or critica	al hazards.
Developmental effects	known significant effects or critica	al hazards.
Fertility effects	known significant effects or critica	al hazards.

#### **Numerical measures of toxicity**

#### Acute toxicity estimates

There is no data available.



## Section 12. Ecological information

## **Toxicity**

Product/ingredient name	Result	Species	Exposure
Carbon black, respirable powder	Acute EC50 37.563 mg/L Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
Amines, tallow alkyl, ethoxylated	Acute LC50 2.6 µg/L Fresh water	Crustaceans - Thamnocephalus platyurus	48 hours
		- Nauplii	
	Acute LC50 2350 µg/L Fresh water	Daphnia - Daphnia pulex	48 hours
	Acute LC50 650 µg/L Fresh water	Fish - Oncorhynchus mykiss	96 hours
Carbendazim	Acute EC50 19.0562 mg/L Fresh water	Algae - Scenedesmus acutus var. acutus	96 hours
	Acute EC50 20 µg/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 77 μg/L Fresh water	Crustaceans - Gammarus pulex - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 7 μg/L Fresh water	Fish - Ictalurus punctatus - Yolk-sac fry	96 hours
	Chronic EC10 10 µg/L Fresh water	Crustaceans - Gammarus pulex - Adult	21 days
	Chronic NOEC 3.1 ppb Fresh water	Daphnia - Daphnia magna	21 days
-lodo-2-propynyl butylcarbamate	Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca	48 hours
	Acute LC50 40 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 67 μg/L Fresh water	Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 8.4 ppb	Fish - Pimephales promelas	35 days
l'-tert-butyl-N-cyclopropyl-6- methylthio)-1,3,5-triazine-2,4-diamine	Acute EC50 0.098 µg/L Marine water	Algae - Fibrocapsa japonica	72 hours
	Acute EC50 0.056 µg/L Fresh water	Algae - Ulnaria ulna	96 hours
	Acute EC50 5.3 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.556 mg/L Marine water	Crustaceans - Balanus albicostatus - Nauplii	48 hours
	Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic EC10 0.0018 µg/L Fresh water	Algae - Ulnaria ulna	96 hours
	Chronic NOEC 0.58 to 0.61 µg/L Marine water	Aquatic plants - Plantae	96 hours
	Chronic NOEC 0.17 ppm	Fish - Cyprinodon variegatus	33 days
Chromium	Acute EC50 0.2 ppm Marine water	Algae - Bacillariophyta	72 hours
	Acute EC50 5 ppm Marine water	Algae - Macrocystis pyrifera - Young	4 days
	Acute EC50 35000 µg/L Fresh water	Aquatic plants - Lemna minor	4 days
	Acute LC50 45 µg/L Fresh water	Crustaceans - Ceriodaphnia reticulata	48 hours
	Acute LC50 22 µg/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 13.9 ppm Fresh water	Fish - Anguilla rostrata	96 hours
	Chronic NOEC 50 mg/L Marine water	Algae - Glenodinium halli	72 hours
	Chronic NOEC 0.19 µg/L Fresh water	Fish - Cyprinus carpio	4 weeks

#### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Carbendazim	1.52	2.51	low

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.





## Section 13. Disposal considerations

**Disposal methods** 

DOT-RO Dotaile

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

10 lbs / 4 54 kg

## Section 14. Transport information

Carbondazim

DOT Classification	<b>TDG Classification</b>	IMDG	ΙΑΤΑ
UN3082	UN3082	UN3082	UN3082
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate). Marine pollutant (Amines, tallow alkyl, ethoxylated)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate). Marine pollutant (Amines, tallow alkyl, ethoxylated)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate)
9	9	9	9
Ш	111	Ш	Ш
Yes.	Yes.	Yes.	Yes.
	UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate) 9 9 U	UN3082     UN3082       ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate)     ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate). Marine pollutant (Amines, tallow alkyl, ethoxylated)       9     9       III     III	UN3082     UN3082     UN3082       ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate)     ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate). Marine pollutant (Amines, tallow alkyl, ethoxylated)     ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Carbendazim, 3-lodo-2-propynyl butylcarbamate). Marine pollutant (Amines, tallow alkyl, ethoxylated)       9     9       III     III

**AERG** : 171

Dor rig Dotano		10 100 / 4.04 Ng
Additional information		
DOT Classification	sizes less than the produc The marine pollutant mark sizes of ≤5 L or ≤5 kg. <b>Reportable quantity</b> 3748	product are not regulated as hazardous materials in packag t reportable quantity, unless transported by inland waterway is not required when transported on inland waterways in 36.9 lbs / 17019 kg [4281.9 gal / 16208.6 L]. Package sizes than the product reportable quantity are not subject to the Re portation requirements.
TDG Classification	Goods Regulations: 2.43-2	he following sections of the Transportation of Dangerous 2.45 (Class 9), 2.7 (Marine pollutant mark). product are not regulated as dangerous goods when
IMDG		ed as a dangerous good when transported in sizes of ≤5 L o gings meet the general provisions of 4.1.1.1, 4.1.1.2 and -A, S-B
ΙΑΤΑ		ed as a dangerous good when transported in sizes of ≤5 L o gings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 ar
	Tol: +1 888 CHS 7760 (	447 7760) / ±1 450 GHS 7767 (447 7767)

Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



## Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

# Section 15. Regulatory information

U.S. Federal regulations	: United States inventory (TSCA 8b): All components are listed or exempted.
	Clean Water Act (CWA) 307: Chromium
	Clean Water Act (CWA) 311: Triethylamine; Acetaldehyde
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed

#### SARA 302/304

#### Composition/information on ingredients

		SARA 302 TPQ SARA 304 RQ		Q	
Name	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ethylene oxide	Yes.	1000	-	10	-

## **SARA 304 RQ**

: 1984127 lbs / 900793.7 kg [226632.9 gal / 857898.7 L]

#### SARA 311/312

Classification : CARCINOGENICITY - Category 2

#### Composition/information on ingredients

Name	Classification
Carbon black, respirable powder	CARCINOGENICITY - Category 2

#### **SARA 313**

There is no data available.

#### State regulations

- Massachusetts
- **New York**

- : The following components are listed: Diiron trioxide
- : None of the components are listed.
- **New Jersey**

- The following components are listed: Carbon black, respirable powder; Diiron trioxide 2
- : The following components are listed: Carbon black, respirable powder; Diiron trioxide
- Pennsylvania California Prop. 65





## Section 15. Regulatory information

**WARNING**: This product can expose you to chemicals including Ethylene oxide and 4-Methylpentan-2-one, which are known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Carbon black, respirable powder, Crystalline silica, respirable powder, Acetaldehyde and 1,4-Dioxane, which are known to the State of California to cause cancer, and N-methyl-2-pyrrolidone and Ethanediol, which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### Canada

**Canadian lists** 

- **Canadian NPRI**
- : None of the components are listed.
- **CEPA Toxic substances**
- : None of the components are listed.
- c substances : None of the

Canada inventory (DSL NDSL)

- : Not determined.

## Section 16. Other information

#### Procedure used to derive the classification

Classification	Justification
AQUATIC HAZARD (ACUTE) - Category 1	Calculation method Calculation method Calculation method

<u>History</u>	
Date of issue mm/dd/yyyy	: 12/15/2019
Date of previous issue	: 05/15/2018
Version	: 4
Prepared by	: KMK Regulatory Services Inc.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

