



Scan QR code to compare GF products.

Enduro Tintable 2K Clear Poly	Enduro Tintable 2K White Poly	Enduro 2K Conversion Varnish	Enduro 1K Clear Poly	Enduro 1K White Poly	Enduro 1K Pre-Cat Lacquer	Enduro 1K Sanding Sealer
						
2-Component, Tintable Water-based Urethane	2-Component, Tintable Water-based Urethane	Catalyzed, Most Durable Interior/Exterior Clear	Spray-Only, Durable Clear	Spray-Only, Durable Pigmented	Production Shops, Fast Stack Times, Economical Price	Fast Building, Easier Sanding, Economical Price
SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE
Interior & Exterior Commercial Furniture, Doors, Cabinets, Millwork, Fiberglass, Pre-Primed Steel	Interior & Exterior Commercial Furniture, Doors, Cabinets, Millwork, Fiberglass, Pre-Primed Steel	Commercial Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork
AMBERING	AMBERING	AMBERING	AMBERING	AMBERING	AMBERING	AMBERING
No	No	No	No	No	No	No
SHEEN	SHEEN	SHEEN	SHEEN	SHEEN	SHEEN	SHEEN
Flat (≤10), Satin (25-35), Semi-Gloss (50-60), Gloss (90+)	Flat (≤10), Satin (25-35), Semi-Gloss (50-60), Gloss (80+)	Flat (≤10), Satin (25-35), Semi-Gloss (50-60), Gloss (80+)	Dead Flat (<5), Flat (≤10), Satin (25-35), Semi-Gloss (50-60), Gloss (80+)	Flat (≤10), Satin (25-35), Semi-Gloss (50-60)	Flat (≤10), Satin (25-35), Semi-Gloss (50-60), Gloss (80+)	N/A
INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR
Interior & Exterior, No Decks	Interior & Exterior, No Decks	Interior & Exterior, No Decks	Interior Only	Interior Only	Interior Only	Interior Only
TYPE	TYPE	TYPE	TYPE	TYPE	TYPE	TYPE
Urethane	Urethane	Urethane/Acrylic Blend	Urethane/Acrylic Blend	Pigmented Urethane/Acrylic Blend	Self-Crosslinking Acrylic	Acrylic
CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES
Gallons, 5 Gallon	Gallons, 5 Gallon	Gallons, 5 Gallon	Gallons, 5 Gallon*	Gallons, 5 Gallon*	Gallons, 5 Gallon	Quarts, Gallons, 5 Gallon*
COVERAGE	COVERAGE	COVERAGE	COVERAGE	COVERAGE	COVERAGE	COVERAGE
450 Sq. Ft./Gal.	450 Sq. Ft./Gal.	450 Sq. Ft./Gal.	450 Sq. Ft./Gal.	450 Sq. Ft./Gal.	400 Sq. Ft./Gal.	400-500 Sq. Ft./Gal.
COATS	COATS	COATS	COATS	COATS	COATS	COATS
2-3 Coats	2-3 Coats	3 Coats	3 Coats	3 Coats	3 Coats	1-2 Coats
APPLICATION	APPLICATION	APPLICATION	APPLICATION	APPLICATION	APPLICATION	APPLICATION
Spray	Spray	Spray	Spray	Spray	Spray	Brush, Roll, Spray
OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES
Yes	Yes	Yes	Yes	Yes	Yes	Yes
TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE
HVLP 1.1mm-1.3mm	HVLP 1.1mm-1.3mm	HVLP 1.1mm-1.3mm	HVLP 1.1mm-1.3mm	HVLP 1.1mm-1.5mm	HVLP 1.1mm-1.3mm	HVLP .043mm-.051mm
DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH
30+ Min.	30+ Min.	30+ Min.	30+ Min.	30+ Min.	10+ Min.	10+ Min.
DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT
30-45+ Min.	1+ Hr.	2+ Hr.	1+ Hr.	2+ Hr.	1+ Hr.	1+ Hr.
STACK TIMES 70°F, 50% RH	STACK TIMES 70°F, 50% RH	STACK TIMES 70°F, 50% RH	STACK TIMES 70°F, 50% RH	STACK TIMES 70°F, 50% RH	STACK TIMES 70°F, 50% RH	STACK TIMES 70°F, 50% RH
					12+ Hours Dependent on Conditions	N/A
DRY TIME - CURE	DRY TIME - CURE	DRY TIME - CURE	DRY TIME - CURE	DRY TIME - CURE	DRY TIME - CURE	DRY TIME - CURE
5 Days	5 Days	5 Days	21 Days	21 Days	21 Days	21 Days
DURABILITY	DURABILITY	DURABILITY	DURABILITY	DURABILITY	DURABILITY	DURABILITY
Highest	Highest	Highest	High	High	Medium	Medium
WATER RESISTANCE	WATER RESISTANCE	WATER RESISTANCE	WATER RESISTANCE	WATER RESISTANCE	WATER RESISTANCE	WATER RESISTANCE
5	5	5	5	5	5	3
CHEMICAL RESISTANCE	CHEMICAL RESISTANCE	CHEMICAL RESISTANCE	CHEMICAL RESISTANCE	CHEMICAL RESISTANCE	CHEMICAL RESISTANCE	CHEMICAL RESISTANCE
101	101	101	98	88	89	91
VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY
Thick	Thick	Medium	Medium	Medium	Medium	Medium
WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS
28%-33%	42%-46%	28%-29%	28%-33%	44%-45%	24%-26%	30%
VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS
26%-30%	30%-35%	26%-27%	25%-35%	32%-33%	23%-24%	N/A
VOC	VOC	VOC	VOC	VOC	VOC	VOC
<250 g/L	<200 g/L	<197 g/L	<233 g/L	<210 g/L	<271 g/L	<122 g/L