



General Finishes Paints & Pigmented Topcoat Product Comparison Chart



ENDURO

BY GENERAL FINISHES

Milk Paint	Glaze Effects	Enduro 1K Pigmented White Poly	Enduro 1K Pigmented Black Poly	Enduro Tintable 2K White Poly
				
Interior & Exterior Flat Paint	For Creating Artistic Features	Interior Spray-Only White Enamel	Interior Spray-Only Black Enamel	Interior & Exterior Spray-Only Tintable 2K Urethane
SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE	SUGGESTED USE
Furniture, Cabinets, Millwork	Furniture, Cabinets, Millwork	White Furniture, Cabinets, Millwork	Black Furniture, Cabinets, Millwork	Interior & Exterior Commercial Furniture, Doors, Cabinets, Millwork, Fiberglass, Pre-Primed Steel
PRODUCT COLOR	PRODUCT COLOR	PRODUCT COLOR	PRODUCT COLOR	PRODUCT COLOR
12 Stock Colors, Clear & White Bases	Burnt Umber, Pitch Black, Van Dye Brown, Winter White, Smokey Gray & Clear Base	White, Tintable	Black	White, Tintable
AMBERING	AMBERING	AMBERING	AMBERING	AMBERING
No	No	No	No	No
SHEEN	SHEEN	SHEEN	SHEEN	SHEEN
Flat low luster (10-15)	N/A	Flat (≤ 10), Satin (25-35), Semi-Gloss (50-60)	Satin (25-35), Semi-Gloss (50-60)	Flat (≤ 10), Satin (25-35), Semi-Gloss (50-60), Gloss (80+)
INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR	INTERIOR OR EXTERIOR
Interior & Exterior	Interior Only	Interior Only	Interior Only	Interior & Exterior
TYPE	TYPE	TYPE	TYPE	TYPE
Acrylic Paint	Glaze	Urethane/Acrylic Blend	Urethane/Acrylic Blend	Urethane
CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES	CAN SIZES
Pints, Quarts, Gallons, 5 Gallon	Pints, Quarts, Gallons	Quarts, Gallons, 5 Gallon*	Gallons, 5 Gallon*	Gallons, 5 Gallon
COVERAGE	COVERAGE	COVERAGE	COVERAGE	COVERAGE
400-500 Sq. Ft./Gal.	480-640 Sq. Ft./Gal.	450 Sq. Ft./Gal.	450 Sq. Ft./Gal.	450 Sq. Ft./Gal.
COATS	COATS	COATS	COATS	COATS
1+ Coats	1+ Coats	3 Coats	3 Coats	2-3 Coats
APPLICATION	APPLICATION	APPLICATION	APPLICATION	APPLICATION
Brush, Roll, Spray, Pad	Brush, Spray	Spray	Spray	Spray
OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES	OVER EXISTING FINISHES
Yes	Yes	Yes	Yes	Yes
TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE	TIP SIZE
HVLP 1.8mm-2.0mm	HVLP 1.3mm-2.0mm	HVLP 1.3mm-1.5mm	HVLP 1.3mm-1.5mm	HVLP 1.1mm-1.3mm
DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH	DRY TIME - TOUCH
30+ Min.	1+ Hr.	30+ Min.	30+ Min.	30+ Min.
DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT	DRY TIME - RECOAT
2+ Hr.	3+ Hr.	2+ Hr.	2+ Hr.	1+ Hr.
DRY TIME - CURE	DRY TIME - CURE	DRY TIME - CURE	DRY TIME - CURE	DRY TIME - CURE
21 Days	N/A	21 Days	21 Days	5 Days
DURABILITY	DURABILITY	DURABILITY	DURABILITY	DURABILITY
High	N/A	High	High	Highest
WATER RESISTANCE	WATER RESISTANCE	WATER RESISTANCE	WATER RESISTANCE	WATER RESISTANCE
Varies by Color	N/A	5	5	5
CHEMICAL RESISTANCE	CHEMICAL RESISTANCE	CHEMICAL RESISTANCE	CHEMICAL RESISTANCE	CHEMICAL RESISTANCE
Varies by Color	N/A	88	92	89
VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY
Thick	Medium	Medium	Medium	Medium
WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS	WEIGHT SOLIDS
54%	22%	45%	31%	46%
VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS	VOLUME SOLIDS
47%	N/A	33%	28%	35%
VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY	VISCOSITY
<50 g/L	<304 g/L	<210 g/L	<242 g/L	<200 g/L



GENERAL FINISHES • 2462 Corporate Circle, East Troy, Wisconsin • GeneralFinishes.com

