

# SAFETY DATA SHEET

US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Issuing Date draft

Revision Date 13-Oct-2023

Revision Number 1

1. Identification	
Product identifier	
Product Name	Georgian Cherry Gel Stain
Other means of identification	<u>on</u>
Product Code(s)	B257
Synonyms	None
Recommended use of the c	hemical and restrictions on use
Recommended use	Wood coating
Restrictions on use	Use only for intended applications
Details of the supplier of the	e safety data sheet
Manufacturer Address General Finishes 2462 Coporate Circle East Troy, WI 53120 Phone 1-800-783-6050	DistributorWood Essence2343 1st Ave North, unit BSaskatoon, SK S7K 2A2Phone 306-955-8775Dover Finishing Products180 Ave Du VoyageurPointe-Claire, QC H9R6A8Phone 514-697-3000Lee Valley Tools1090 Morrison DriveOttawa, ON K2H1C2Phone 613-596-0350
Emergency telephone numb	ber
Emergency telephone	24 Hour Emergency Phone Number Chemtrec 1-800-424-9300 +1 703 527 3887 (CHEMTREC International)
2. Hazard(s) identific	ation

# **Classification**

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2B
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

#### Label elements

## Danger

Hazard statements Causes skin irritation. Causes eye irritation. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.



# **Precautionary Statements - Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Wash face, hands and any exposed skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Do not breathe dust, fume, gas, mist, vapors and spray.

Do not eat, drink or smoke when using this product.

# **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention.

## Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

#### Skin

IF ON SKIN: Wash with plenty of soap and water.

Take off contaminated clothing and wash before reuse.

If skin irritation or rash occurs: Get medical advice and attention.

#### **Precautionary Statements - Storage**

Store locked up.

#### **Precautionary Statements - Disposal**

Dispose of contents and container to an approved waste disposal plant.

## Other information

No information available.

# 3. Composition/information on ingredients

#### Substance

Not applicable.

## Mixture

Chemical name	CAS No.	Weight-%	Information Review	Date HMIRA filed and date exemption granted (if applicable)
---------------	---------	----------	--------------------	---

Petroleum distillates, hydrotreated light	64742-47-8	10 - 30	-	-
Solvent naphtha (petroleum), medium aliph.	64742-88-7	10 - 30	-	-
Stoddard solvent	8052-41-3	5 - 10	-	-
Ethanol	64-17-5	1 - 5	-	-
2-Butanone, oxime	96-29-7	0.1 - 1	-	-
Xylene	1330-20-7	0.1 - 1	-	-
Quartz	14808-60-7	0.1 - 1	-	-
Talc	14807-96-6	0.1 - 1	-	-
Carbon black	1333-86-4	0.1 - 1	-	-
Ethylbenzene	100-41-4	0.1 - 1	-	-
Benzaldahyde	100-52-7	0.1 - 1	-	-
Naphtha, petroleum, hydrotreated heavy	64742-48-9	0.1 - 1	-	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. First-aid measures

# **Description of first aid measures**

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Get medical attention if irritation develops and persists. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).
Most important symptoms and effe	cts, both acute and delayed
Symptoms	Itching. Rashes. Hives.
Effects of Exposure	May cause cancer. Mutagenic effects. Causes damage to organs through prolonged or repeated exposure.
Indication of any immediate medica	I attention and special treatment needed
Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
5. Fire-fighting measures	
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	No information available.
Specific hazards arising from the chemical	Product is or contains a sensitizer. May cause sensitization by skin contact.
Explosion data Sensitivity to mechanical impac	t None.

Sensitivity to static discharge None.

Special protective equipment and	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.
precautions for fire-fighters	Use personal protection equipment.

# 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
Other information	Refer to protective measures listed in Sections 7 and 8.
Methods and material for containme	ent and cleaning up
Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.

# 7. Handling and storage

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.

## Conditions for safe storage, including any incompatibilities

Storage ConditionsKeep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.<br/>Keep out of the reach of children. Store away from other materials.

# 8. Exposure controls/personal protection

# Control parameters

# **Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Stoddard solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m <sup>3</sup>
8052-41-3		TWA: 2900 mg/m <sup>3</sup>	Ceiling: 1800 mg/m <sup>3</sup> 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) TWA: 525 mg/m <sup>3</sup>	
Ethanol	STEL: 1000 ppm	TWA: 1000 ppm	IDLH: 3300 ppm
64-17-5		TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1900 mg/m <sup>3</sup>
		(vacated) TWA: 1900 mg/m <sup>3</sup>	
Xylene	TWA: 20 ppm	TWA: 100 ppm	-
1330-20-7		TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m <sup>3</sup>	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m <sup>3</sup>	
Quartz	TWA: 0.025 mg/m <sup>3</sup> respirable		IDLH: 50 mg/m <sup>3</sup> respirable dust
14808-60-7	particulate matter	(vacated) TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup> respirable
		respirable dust	dust

	1					
				SiO2 + 5) mppcf		
				rable fraction		
				O2 + 2) mg/m <sup>3</sup>		
			TWA respir	rable fraction		
Talc	TWA: 2 mg/m <sup>3</sup> parti	iculate	TWA: 20 mppc	f if 1% Quartz		IDLH: 1000 mg/m <sup>3</sup>
14807-96-6	matter containing no a	sbestos	or more, us	e Quartz limit	TWA:	: 2 mg/m <sup>3</sup> containing no
	and <1% crystalline	silica,	(vacated) T	WA: 2 mg/m <sup>3</sup>	Asbe	estos and <1% Quartz
	respirable particulate	matter	respirable dust	<1% Crystalline		respirable dust
			silica, containi	ing no Asbestos		
			TWA: 20 mppc	f if 1% Quartz or		
			more, use	Quartz limit		
Carbon black	TWA: 3 mg/m <sup>3</sup> inha	alable		3.5 mg/m <sup>3</sup>		IDLH: 1750 mg/m <sup>3</sup>
1333-86-4	particulate matte			VA: 3.5 mg/m <sup>3</sup>		TWA: 3.5 mg/m <sup>3</sup>
	P		(********) * *		TWA: 0	.1 mg/m³ Carbon black in
						ce of Polycyclic aromatic
						hydrocarbons PAH
Ethylbenzene	Ototoxicant - potential	to cause	TW/A·	100 ppm		IDLH: 800 ppm
100-41-4	hearing disorder			35 mg/m <sup>3</sup>		TWA: 100 ppm
	TWA: 20 ppm			WA: 100 ppm		TWA: 435 mg/m <sup>3</sup>
	1 W/ 20 pp///			VA: 435 mg/m <sup>3</sup>		STEL: 125 ppm
				TEL: 125 ppm		STEL: 545 mg/m <sup>3</sup>
			Vacated) ST	EL: 545 mg/m <sup>3</sup>		
Chemical name	Alberta	Britis		EL: 545 mg/m <sup>3</sup> Ontario		Quebec
Chemical name Stoddard solvent	Alberta TWA: 100 ppm		h Columbia	Ontario	n/m <sup>3</sup>	
Stoddard solvent	TWA: 100 ppm	TWA	h Columbia : 290 mg/m <sup>3</sup>	<u> </u>	g/m <sup>3</sup>	TWA: 100 ppm
Stoddard solvent 8052-41-3	TWA: 100 ppm TWA: 572 mg/m <sup>3</sup>	TWA STEL	h Columbia : 290 mg/m³ : 580 mg/m³	Ontario TWA: 525 mg	-	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup>
Stoddard solvent 8052-41-3 Ethanol	TWA: 100 ppm TWA: 572 mg/m <sup>3</sup> TWA: 1000 ppm	TWA STEL	h Columbia : 290 mg/m <sup>3</sup>	Ontario	-	TWA: 100 ppm
Stoddard solvent 8052-41-3 Ethanol 64-17-5	TWA: 100 ppm TWA: 572 mg/m <sup>3</sup> TWA: 1000 ppm TWA: 1880 mg/m <sup>3</sup>	TWA STEL STEL	h Columbia : 290 mg/m³ : 580 mg/m³ .: 1000 ppm	Ontario TWA: 525 mg STEL: 1000 j	opm	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup> STEL: 1000 ppm
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene	TWA: 100 ppm           TWA: 572 mg/m³           TWA: 1000 ppm           TWA: 1880 mg/m³           TWA: 100 ppm	TWA STEL STEL TWA	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm	Ontario TWA: 525 m STEL: 1000   TWA: 100 p	opm pm	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 100 ppm
Stoddard solvent 8052-41-3 Ethanol 64-17-5	TWA: 100 ppm           TWA: 572 mg/m³           TWA: 1000 ppm           TWA: 1880 mg/m³           TWA: 100 ppm           TWA: 434 mg/m³	TWA STEL STEL TWA	h Columbia : 290 mg/m³ : 580 mg/m³ .: 1000 ppm	Ontario TWA: 525 mg STEL: 1000 j	opm pm	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 100 ppm TWA: 434 mg/m <sup>3</sup>
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene	TWA: 100 ppm           TWA: 572 mg/m³           TWA: 1000 ppm           TWA: 1880 mg/m³           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm	TWA STEL STEL TWA	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm	Ontario TWA: 525 m STEL: 1000   TWA: 100 p	opm pm	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene 1330-20-7	TWA: 100 ppm           TWA: 572 mg/m³           TWA: 1000 ppm           TWA: 1880 mg/m³           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³	TWA STEL STEL TWA STE	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p	pm pm pm	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene 1330-20-7 Quartz	TWA: 100 ppm           TWA: 572 mg/m³           TWA: 1000 ppm           TWA: 1880 mg/m³           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm	TWA STEL STEL TWA STE	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm	Ontario TWA: 525 m STEL: 1000   TWA: 100 p	pm pm pm	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene 1330-20-7 Quartz 14808-60-7	TWA: 100 ppm           TWA: 572 mg/m³           TWA: 1000 ppm           TWA: 1880 mg/m³           TWA: 100 ppm           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³           TWA: 0.025 mg/m³	TWA STEL STEL TWA STE	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm 0.025 mg/m <sup>3</sup>	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p TWA: 0.10 m	pm pm pm g/m <sup>3</sup>	TWA: 100 ppm           TWA: 525 mg/m³           STEL: 1000 ppm           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³           TWA: 0.1 mg/m³
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene 1330-20-7 Quartz 14808-60-7 Talc	TWA: 100 ppm           TWA: 572 mg/m³           TWA: 1000 ppm           TWA: 1880 mg/m³           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³	TWA STEL STEL TWA STE	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p	pm pm pm g/m <sup>3</sup>	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup> STEL: 1000 ppm TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>
Stoddard solvent 8052-41-3           Ethanol           64-17-5           Xylene           1330-20-7           Quartz           14808-60-7           Talc           14807-96-6	TWA: 100 ppm           TWA: 572 mg/m³           TWA: 1000 ppm           TWA: 1880 mg/m³           TWA: 100 ppm           TWA: 0.025 mg/m³           TWA: 2 mg/m³	TWA STEL TW/ STE TWA: TWA:	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm 0.025 mg/m <sup>3</sup> A: 2 mg/m <sup>3</sup>	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p TWA: 0.10 m TWA: 2 mg/	pm pm pm g/m <sup>3</sup>	TWA: 100 ppm         TWA: 525 mg/m³         STEL: 1000 ppm         TWA: 100 ppm         TWA: 434 mg/m³         STEL: 150 ppm         STEL: 651 mg/m³         TWA: 0.1 mg/m³         TWA: 2 mg/m³
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene 1330-20-7 Quartz 14808-60-7 Talc 14807-96-6 Carbon black	TWA: 100 ppm           TWA: 572 mg/m³           TWA: 1000 ppm           TWA: 1880 mg/m³           TWA: 100 ppm           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³           TWA: 0.025 mg/m³	TWA STEL TW/ STE TWA: TWA:	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm 0.025 mg/m <sup>3</sup>	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p TWA: 0.10 m	pm pm pm g/m <sup>3</sup>	TWA: 100 ppm           TWA: 525 mg/m³           STEL: 1000 ppm           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³           TWA: 0.1 mg/m³
Stoddard solvent 8052-41-3           Ethanol           64-17-5           Xylene           1330-20-7           Quartz           14808-60-7           Talc           14807-96-6           Carbon black           1333-86-4	TWA: 100 ppm         TWA: 572 mg/m³         TWA: 1000 ppm         TWA: 1880 mg/m³         TWA: 100 ppm         TWA: 434 mg/m³         STEL: 150 ppm         STEL: 651 mg/m³         TWA: 0.025 mg/m³         TWA: 2 mg/m³         TWA: 3.5 mg/m³	TWA STEL STEL TW/ STE TWA: TW/	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm 0.025 mg/m <sup>3</sup> A: 2 mg/m <sup>3</sup> A: 3 mg/m <sup>3</sup>	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p TWA: 0.10 m TWA: 2 mg/	pm pm pm g/m <sup>3</sup> (m <sup>3</sup>	TWA: 100 ppm           TWA: 525 mg/m³           STEL: 1000 ppm           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³           TWA: 0.1 mg/m³           TWA: 2 mg/m³           TWA: 3 mg/m³
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene 1330-20-7 Quartz 14808-60-7 Talc 14807-96-6 Carbon black 1333-86-4 Ethylbenzene	TWA: 100 ppm         TWA: 572 mg/m³         TWA: 1000 ppm         TWA: 1880 mg/m³         TWA: 100 ppm         TWA: 434 mg/m³         STEL: 150 ppm         STEL: 651 mg/m³         TWA: 0.025 mg/m³         TWA: 2 mg/m³         TWA: 3.5 mg/m³         TWA: 100 ppm	TWA STEL STEL TW/ STE TWA: TW/	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm 0.025 mg/m <sup>3</sup> A: 2 mg/m <sup>3</sup>	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p TWA: 0.10 m TWA: 2 mg/	pm pm pm g/m <sup>3</sup> (m <sup>3</sup>	TWA: 100 ppm         TWA: 525 mg/m³         STEL: 1000 ppm         TWA: 100 ppm         TWA: 434 mg/m³         STEL: 150 ppm         STEL: 651 mg/m³         TWA: 0.1 mg/m³         TWA: 2 mg/m³
Stoddard solvent 8052-41-3           Ethanol           64-17-5           Xylene           1330-20-7           Quartz           14808-60-7           Talc           14807-96-6           Carbon black           1333-86-4	TWA: 100 ppm         TWA: 572 mg/m³         TWA: 1000 ppm         TWA: 100 ppm         TWA: 434 mg/m³         STEL: 651 mg/m³         TWA: 0.025 mg/m³         TWA: 2 mg/m³         TWA: 3.5 mg/m³         TWA: 100 ppm         TWA: 434 mg/m³	TWA STEL STEL TW/ STE TWA: TW/	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm 0.025 mg/m <sup>3</sup> A: 2 mg/m <sup>3</sup> A: 3 mg/m <sup>3</sup>	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p TWA: 0.10 m TWA: 2 mg/	pm pm pm g/m <sup>3</sup> (m <sup>3</sup>	TWA: 100 ppm           TWA: 525 mg/m³           STEL: 1000 ppm           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³           TWA: 0.1 mg/m³           TWA: 2 mg/m³           TWA: 3 mg/m³
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene 1330-20-7 Quartz 14808-60-7 Talc 14807-96-6 Carbon black 1333-86-4 Ethylbenzene	TWA: 100 ppm         TWA: 572 mg/m³         TWA: 1000 ppm         TWA: 100 ppm         TWA: 434 mg/m³         STEL: 651 mg/m³         TWA: 0.025 mg/m³         TWA: 2 mg/m³         TWA: 3.5 mg/m³         TWA: 100 ppm         TWA: 100 ppm         TWA: 100 ppm         STEL: 125 ppm	TWA STEL STEL TW/ STE TWA: TW/	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm 0.025 mg/m <sup>3</sup> A: 2 mg/m <sup>3</sup> A: 3 mg/m <sup>3</sup>	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p TWA: 0.10 m TWA: 2 mg/	pm pm pm g/m <sup>3</sup> (m <sup>3</sup>	TWA: 100 ppm           TWA: 525 mg/m³           STEL: 1000 ppm           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³           TWA: 0.1 mg/m³           TWA: 2 mg/m³           TWA: 3 mg/m³
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene 1330-20-7 Quartz 14808-60-7 Talc 14807-96-6 Carbon black 1333-86-4 Ethylbenzene 100-41-4	TWA: 100 ppm         TWA: 572 mg/m³         TWA: 1000 ppm         TWA: 100 ppm         TWA: 434 mg/m³         STEL: 651 mg/m³         TWA: 0.025 mg/m³         TWA: 2 mg/m³         TWA: 3.5 mg/m³         TWA: 100 ppm         TWA: 434 mg/m³	TWA STEL STEL TW/ STE TWA: TW/	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm 0.025 mg/m <sup>3</sup> A: 2 mg/m <sup>3</sup> A: 3 mg/m <sup>3</sup>	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p TWA: 0.10 m TWA: 2 mg/ TWA: 3 mg/ TWA: 20 pp	pm pm pm g/m <sup>3</sup> (m <sup>3</sup> om	TWA: 100 ppm           TWA: 525 mg/m³           STEL: 1000 ppm           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³           TWA: 0.1 mg/m³           TWA: 2 mg/m³           TWA: 3 mg/m³
Stoddard solvent 8052-41-3 Ethanol 64-17-5 Xylene 1330-20-7 Quartz 14808-60-7 Talc 14807-96-6 Carbon black 1333-86-4 Ethylbenzene	TWA: 100 ppm         TWA: 572 mg/m³         TWA: 1000 ppm         TWA: 100 ppm         TWA: 434 mg/m³         STEL: 651 mg/m³         TWA: 0.025 mg/m³         TWA: 2 mg/m³         TWA: 3.5 mg/m³         TWA: 100 ppm         TWA: 100 ppm         TWA: 100 ppm         STEL: 125 ppm	TWA STEL STEL TW/ STE TWA: TW/	h Columbia : 290 mg/m <sup>3</sup> : 580 mg/m <sup>3</sup> : 1000 ppm A: 100 ppm L: 150 ppm 0.025 mg/m <sup>3</sup> A: 2 mg/m <sup>3</sup> A: 3 mg/m <sup>3</sup>	Ontario TWA: 525 m STEL: 1000 p TWA: 100 p STEL: 150 p TWA: 0.10 m TWA: 2 mg/	2 pm pm pm g/m <sup>3</sup> (m <sup>3</sup> m pm m	TWA: 100 ppm           TWA: 525 mg/m³           STEL: 1000 ppm           TWA: 100 ppm           TWA: 434 mg/m³           STEL: 150 ppm           STEL: 651 mg/m³           TWA: 0.1 mg/m³           TWA: 2 mg/m³           TWA: 3 mg/m³

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Stoddard solvent	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
Ethanol	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
Xylene	TWA: 20 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 20 ppm	TWA: 20 ppm
Quartz	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>
Talc	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Carbon black	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
Ethylbenzene	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Stoddard solvent	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
	STEL: 125 ppm		STEL: 125 ppm	TWA: 575 mg/m <sup>3</sup>

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
				STEL: 150 ppm STEL: 720 mg/m <sup>3</sup>
Ethanol	TWA: 1000 ppm STEL: 1250 ppm	STEL: 1000 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 1900 mg/m <sup>3</sup>
Xylene	TWA: 100 ppm STEL: 150 ppm	TWA: 20 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 150 ppm STEL: 650 mg/m <sup>3</sup> Skin
Quartz	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 300 particle/mL
Talc	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 20 mppcf
Carbon black	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>
Ethylbenzene	TWA: 100 ppm STEL: 125 ppm Designated substance	TWA: 20 ppm	TWA: 100 ppm STEL: 125 ppm Designated Chemical Substance	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

# **Biological occupational exposure limits**

Chemical name	ACGIH	
Xylene	1.5 g/g creatinine - urine (Methylhippuric acids) - end of	
1330-20-7	shift	
Ethylbenzene	0.15 g/g creatinine - urine (Sum of mandelic acid and	
100-41-4	phenylglyoxylic acid) - end of shift	

# Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.
Individual protection measures, su	ch as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles).
Hand protection	Wear suitable gloves. Impervious gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

# 9. Physical and chemical properties

# Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Color	Red / Brown
Odor	Slight

Odor threshold	No information available	
<u>Property</u> pH Melting point / freezing point Initial boiling point and boiling rang Flash point Evaporation rate Flammability	<u>Values</u> je	Remarks • Method No data available No data available No data available No data available No data available No data available
Flammability Limit in Air Upper flammability or explosive limits		No data available
Lower flammability or explosive limits		No data available
Vapor pressure Relative vapor density Relative density Water solubility	7.75 Insoluble in water	No data available No data available
Solubility(ies) Partition coefficient Autoignition temperature Decomposition temperature		No data available No data available No data available No data available
Kinematic viscosity Dynamic viscosity	900 - 1200 cP	No data available
Other information Explosive properties Oxidizing properties Softening point Molecular weight VOC content VOC Liquid Density Bulk density	No information available. No information available. No information available No information available < 500 g/L No information available No information available	

# 10. Stability and reactivity

Reactivity	None under normal use conditions.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	None known based on information supplied.
Incompatible materials	Strong acids, Strong bases, Strong oxidizing agents.

Hazardous decomposition products None known based on information supplied.

# **11. Toxicological information**

# Information on likely routes of exposure

**Product Information** 

Inhalation	May cause irritation of respiratory tract. Specific test data for the substance or mixture is not available.
Eye contact	Causes eye irritation (based on components). May cause redness, itching, and pain. Specific test data for the substance or mixture is not available.

Skin contact	Causes skin irritation (based on components). Repeated exposure may cause skin dryness or cracking. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Specific test data for the substance or mixture is not available.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Specific test data for the substance or mixture is not available.

# Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

#### Numerical measures of toxicity

# The following values are calculated based on chapter 3.1 of the GHS document:

ATEmix (oral)	166,464.00 mg/kg
ATEmix (dermal)	5,981.30 mg/kg
ATEmix (inhalation-vapor)	79.00 mg/l
ATEmix (inhalation-dust/mist)	16.5236 mg/l

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
Solvent naphtha (petroleum), medium aliph.	> 25 mL/kg (Rat)	> 4000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h
Stoddard solvent	-	> 3000 mg/kg (Rabbit)	> 5.5 mg/L (Rat)4 h
Ethanol	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat)4 h = 133.8 mg/L (Rat)4 h
2-Butanone, oxime	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat)4 h
Xylene	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h
Carbon black	> 15400 mg/kg (Rat)	-	> 4.6 mg/m³ (Rat)4 h
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat)4 h
Benzaldahyde	= 1300 mg/kg (Rat)	> 1250 mg/kg (Rabbit)	-
Naphtha, petroleum, hydrotreated heavy	> 6000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 8500 mg/m³ (Rat)4 h

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Causes skin irritation. Classification based on data available for ingredients.
Serious eye damage/eye irritation	Causes eye irritation. Classification based on data available for ingredients.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	May cause genetic defects. Contains a known or suspected mutagen. Classification based on data available for ingredients.

# Carcinogenicity

May cause cancer. Contains a known or suspected carcinogen. Classification based on data available for ingredients.

The table below indicates whe	her each agency has listed ar	ny ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethanol 64-17-5	A3	Group 1	Known	X
Xylene 1330-20-7	-	Group 3	-	-
Quartz 14808-60-7	A2	Group 1	Known	X
Talc 14807-96-6	-	Group 3	-	X
Carbon black 1333-86-4	A3	Group 2B	-	Х
Ethylbenzene 100-41-4	A3	Group 2B	-	Х

# Legend

<ul> <li>ACGIH (American Conference of Governmental Industrial Hygienists)</li> <li>A2 - Suspected Human Carcinogen</li> <li>A3 - Animal Carcinogen</li> <li>IARC (International Agency for Research on Cancer)</li> <li>Group 1 - Carcinogenic to Humans</li> <li>Group 2B - Possibly Carcinogenic to Humans</li> <li>Group 3 - Not Classifiable as to Carcinogenicity in Humans</li> <li>NTP (National Toxicology Program)</li> <li>Known - Known Carcinogen</li> <li>OSHA (Occupational Safety and Health Administration of the US Department of Labor)</li> <li>X - Present</li> </ul>				
Reproductive toxicity	No information available.			
STOT - single exposure	No information available.			
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.			
Aspiration hazard	No information available.			

# 12. Ecological information

# Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum distillates, hydrotreated light 64742-47-8	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss)	-	-
Solvent naphtha (petroleum), medium aliph. 64742-88-7	EC50: =450mg/L (96h, Pseudokirchneriella subcapitata)	LC50: =800mg/L (96h, Pimephales promelas)	-	EC50: >100mg/L (48h, Daphnia magna)
Ethanol 64-17-5	-	LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 -	-	LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)

		15100mg/L (96h,		
		Pimephales promelas)		
2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: =760mg/L (96h, Poecilia reticulata)	-	EC50: =750mg/L (48h, Daphnia magna)
Xylene 1330-20-7	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h,	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)
Talc	-	Poecilia reticulata) LC50: >100g/L (96h,	-	-
14807-96-6		Brachydanio rerio)		
Ethylbenzene 100-41-4	EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)
Benzaldahyde 100-52-7	-	LC50: 10.6 - 11.8mg/L (96h, Oncorhynchus mykiss) LC50: =12.69mg/L (96h, Oncorhynchus mykiss) LC50: 0.8 - 1.44mg/L (96h, Lepomis macrochirus) LC50: 6.8 - 8.53mg/L (96h, Pimephales	-	-

		promelas) LC50: =7.5mg/L (96h, Lepomis macrochirus)		
Naphtha, petroleum, hydrotreated heavy 64742-48-9	-	LC50: =2200mg/L (96h, Pimephales promelas)	-	-

Persistence and degradability

No information available.

## Bioaccumulation

#### **Component Information**

Chemical name	Partition coefficient
Stoddard solvent 8052-41-3	6.4
Ethanol 64-17-5	-0.35
2-Butanone, oxime 96-29-7	0.65
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.6
Benzaldahyde 100-52-7	1.4

Other adverse effects

No information available.

13. Disposal considerations		
Disposal methods		
Waste from residues/unused products	Dispose of in accordance with local regulations, Dispose of waste in accordance with environmental legislation.	

Contaminated packaging	Do not reuse empty containers.

California waste information	This product contains one or more substances that are listed with the State of California as
	a hazardous waste.

# 14. Transport information

DOT	Not regulated
TDG	Not regulated
IATA	Not regulated
IMDG	Not regulated

# 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

# **International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

## The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

#### International Inventories

Contact supplier for inventory compliance status

#### US Federal Regulations

#### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1.0
Ethylbenzene - 100-41-4	0.1

### SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethylbenzene 100-41-4	1000 lb	Х	Х	Х

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

#### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65	
Ethanol - 64-17-5	Carcinogen	
	Developmental	
Quartz - 14808-60-7	Carcinogen	
Carbon black - 1333-86-4	Carcinogen	
Ethylbenzene - 100-41-4	Carcinogen	
Cumene - 98-82-8	Carcinogen	
Toluene - 108-88-3	Developmental	

Naphthalene - 91-20-3	Carcinogen	
Benzene - 71-43-2	Carcinogen	
	Developmental	
	Male Reproductive	

# U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Stoddard solvent 8052-41-3	Х	X	X
Ethanol 64-17-5	Х	X	X
Xylene 1330-20-7	Х	X	X
Quartz 14808-60-7	Х	X	X
Magnesium carbonate 546-93-0	Х	X	-
Iron oxide 1309-37-1	Х	X	X
Talc 14807-96-6	Х	X	X
Carbon black 1333-86-4	Х	X	X
Ethylbenzene 100-41-4	Х	X	X
Benzaldahyde 100-52-7	Х	X	X
Cumene 98-82-8	Х	X	X
Toluene 108-88-3	Х	X	X
Naphthalene 91-20-3	Х	X	X
Benzene 71-43-2	Х	X	X

# U.S. EPA Label Information

# EPA Pesticide Registration Number Not applicable

16. Other information					
NFPA HMIS Chronic Haza		n <b>mability</b> 0 n <b>mability</b> 0 Hazard	Instability 0 Physical hazards 0	Special hazards - Personal protection X	
Key or lege	nd to abbreviations and acronyms used in	the safety data	sheet		
<u>Legend Ser</u> TWA Ceiling +	ction 8: Exposure controls/personal protection TWA (time-weighted average) Maximum limit value Sensitizers	nSTEL *	STEL (Short Tern Skin designation	n Exposure Limit)	
U.Ś. Enviror	re references and sources for data used to mental Protection Agency ChemView Databa		DS		

European Food Safety Authority (EFSA)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s)) U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act U.S. Environmental Protection Agency High Production Volume Chemicals Food Research Journal Hazardous Substance Database International Uniform Chemical Information Database (IUCLID) Japan GHS Classification Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS) NIOSH (National Institute for Occupational Safety and Health) National Library of Medicine's ChemID Plus (NLM CIP) National Toxicology Program (NTP) New Zealand's Chemical Classification and Information Database (CCID) Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program Organization for Economic Co-operation and Development Screening Information Data Set World Health Organization loouing Date draft

Issuing Date	draft
Revision Date	13-Oct-2023
Revision Note	Initial Release.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet