



# SAFETY DATA SHEET

US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Issuing Date draft

Revision Date 13-Oct-2023

Revision Number 1

## 1. Identification

### Product identifier

Product Name Gray Gel Stain

### Other means of identification

Product Code(s) B488

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended use Wood coating

Restrictions on use Use only for intended applications

### Details of the supplier of the safety data sheet

#### Manufacturer Address

General Finishes  
2462 Coporate Circle  
East Troy, WI 53120  
Phone 1-800-783-6050

#### Distributor

Wood Essence  
2343 1st Ave North, unit B  
Saskatoon, SK S7K 2A2  
Phone 306-955-8775

Dover Finishing Products  
180 Ave Du Voyageur  
Pointe-Claire, QC H9R6A8  
Phone 514-697-3000

Lee Valley Tools  
1090 Morrison Drive  
Ottawa, ON K2H1C2  
Phone 613-596-0350

### Emergency telephone number

Emergency telephone 24 Hour Emergency Phone Number  
Chemtrec 1-800-424-9300  
+1 703 527 3887 (CHEMTREC International)

## 2. Hazard(s) identification

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

**Label elements****Danger****Hazard statements**

Causes skin irritation.  
 Causes serious eye irritation.  
 May cause an allergic skin reaction.  
 May cause genetic defects.  
 May cause cancer.  
 Causes damage to organs.  
 Causes damage to organs through prolonged or repeated exposure.

**Precautionary Statements - Prevention**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Use personal protective equipment as required.  
 Wash face, hands and any exposed skin thoroughly after handling.  
 Contaminated work clothing should not be allowed out of the workplace.  
 Do not breathe dust, fume, gas, mist, vapors and spray.  
 Do not eat, drink or smoke when using this product.

**Precautionary Statements - Response**

IF exposed: Call a POISON CENTER or doctor.

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

**Skin**

IF ON SKIN: Wash with plenty of soap and water.  
 Take off contaminated clothing and wash before reuse.  
 If skin irritation or rash occurs: Get medical advice and attention.

**Precautionary Statements - Storage**

Store locked up.

**Precautionary Statements - Disposal**

Dispose of contents and container to an approved waste disposal plant.

**Other information**

No information available.

**3. Composition/information on ingredients****Substance**

Not applicable.

**Mixture**

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review	Date HMIRA filed and date exemption
---------------	---------	----------	---------------------------------------	-------------------------------------

			Act registry number (HMIRA registry #)	granted (if applicable)
Petroleum distillates, hydrotreated light	64742-47-8	10 - 30	-	-
Titanium dioxide	13463-67-7	10 - 30	-	-
Solvent naphtha (petroleum), medium aliph.	64742-88-7	10 - 30	-	-
Ethanol	64-17-5	1 - 5	-	-
Butanone oxime	96-29-7	0.5 - 1.5	-	-
Stoddard solvent	8052-41-3	0.5 - 1.5	-	-
Carbon black	1333-86-4	0.1 - 1	-	-
Naphtha, petroleum, hydrotreated heavy	64742-48-9	0.1 - 1	-	-
Benzaldehyde	100-52-7	0.1 - 1	-	-
Ethylbenzene	100-41-4	0.1 - 1	-	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First-aid measures

### Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	May cause an allergic skin reaction. If symptoms persist, call a physician. Wash off immediately with soap and plenty of water for at least 15 minutes.
<b>Ingestion</b>	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.
<b>Effects of Exposure</b>	May cause cancer. Mutagenic effects. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	No information available.
<b>Specific hazards arising from the chemical</b>	Product is or contains a sensitizer. May cause sensitization by skin contact.
<b>Explosion data</b>	

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other information** Refer to protective measures listed in Sections 7 and 8.

### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. Handling and storage

### Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.

## 8. Exposure controls/personal protection

### Control parameters

#### Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Titanium dioxide 13463-67-7	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m <sup>3</sup> (vacated)	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup> (vacated)	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup> (vacated)	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in

			presence of Polycyclic aromatic hydrocarbons PAH	
Ethylbenzene 100-41-4	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>	
Chemical name	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Ethanol 64-17-5	TWA: 1000 ppm TWA: 1880 mg/m <sup>3</sup>	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
Stoddard solvent 8052-41-3	TWA: 100 ppm TWA: 572 mg/m <sup>3</sup>	TWA: 290 mg/m <sup>3</sup> STEL: 580 mg/m <sup>3</sup>	TWA: 525 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 525 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
Benzaldehyde 100-52-7	-	-	STEL: 4 ppm STEL: 17 mg/m <sup>3</sup>	-
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Titanium dioxide	TWA: 0.2 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup>
Ethanol	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
Stoddard solvent	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
Carbon black	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
Ethylbenzene	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Titanium dioxide	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>	TWA: 0.2 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>	TWA: 30 mppcf TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
Ethanol	TWA: 1000 ppm STEL: 1250 ppm	STEL: 1000 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> STEL: 1000 ppm STEL: 1900 mg/m <sup>3</sup>
Stoddard solvent	TWA: 100 ppm STEL: 125 ppm	TWA: 100 ppm	TWA: 100 ppm STEL: 125 ppm	TWA: 100 ppm TWA: 575 mg/m <sup>3</sup> STEL: 150 ppm STEL: 720 mg/m <sup>3</sup>
Carbon black	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>
Ethylbenzene	TWA: 100 ppm STEL: 125 ppm Designated substance	TWA: 20 ppm	TWA: 100 ppm STEL: 125 ppm Designated Chemical Substance	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

**Biological occupational exposure limits**

Chemical name	ACGIH
Ethylbenzene	0.15 g/g creatinine - urine (Sum of mandelic acid and

100-41-4	phenylglyoxylic acid) - end of shift
----------	--------------------------------------

**Appropriate engineering controls**

**Engineering controls**                      Showers  
 Eyewash stations  
 Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**                      Wear safety glasses with side shields (or goggles).

**Hand protection**                              Wear suitable gloves. Impervious gloves.

**Skin and body protection**                      Wear suitable protective clothing. Long sleeved clothing.

**Respiratory protection**                      No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations**                      Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

**9. Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

Physical state	Liquid
Color	Gray
Odor	Slight
Odor threshold	No information available

**Property****Values****Remarks • Method**

pH		No data available
Melting point / freezing point		No data available
Initial boiling point and boiling range		No data available
Flash point		No data available
Evaporation rate		No data available
Flammability		No data available
Flammability Limit in Air		
Upper flammability or explosive limits		No data available
Lower flammability or explosive limits		No data available
Vapor pressure		No data available
Relative vapor density		No data available
Relative density	8.1	
Water solubility	Insoluble in water	
Solubility(ies)		No data available
Partition coefficient		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	900 - 1200 cP	

**Other information**

Explosive properties	No information available.
Oxidizing properties	No information available.
Softening point	No information available

<b>Molecular weight</b>	No information available
<b>VOC content</b>	No information available
<b>VOC</b>	< 500 g/L
<b>Liquid Density</b>	No information available
<b>Bulk density</b>	No information available

## 10. Stability and reactivity

<b>Reactivity</b>	None under normal use conditions.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of hazardous reactions</b>	None under normal processing.
<b>Conditions to avoid</b>	None known based on information supplied.
<b>Incompatible materials</b>	Strong acids, Strong bases, Strong oxidizing agents.
<b>Hazardous decomposition products</b>	None known based on information supplied.

## 11. Toxicological information

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	May cause irritation of respiratory tract. Specific test data for the substance or mixture is not available.
<b>Eye contact</b>	Causes serious eye irritation (based on components). May cause redness, itching, and pain. Specific test data for the substance or mixture is not available.
<b>Skin contact</b>	Causes skin irritation (based on components). Repeated exposure may cause skin dryness or cracking. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Specific test data for the substance or mixture is not available.
<b>Ingestion</b>	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Specific test data for the substance or mixture is not available.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Symptoms</b>	Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.
-----------------	---

### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document:

<b>ATEmix (oral)</b>	8,254.80 mg/kg
<b>ATEmix (dermal)</b>	4,866.10 mg/kg
<b>ATEmix (inhalation-vapor)</b>	79.00 mg/l
<b>ATEmix (inhalation-dust/mist)</b>	17.2821 mg/l

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
---------------	-----------	-------------	-----------------

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Titanium dioxide	> 10000 mg/kg ( Rat )	-	= 5.09 mg/L ( Rat ) 4 h
Solvent naphtha (petroleum), medium aliph.	> 25 mL/kg ( Rat )	> 4000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
Ethanol	= 7060 mg/kg ( Rat )	-	= 116.9 mg/L ( Rat ) 4 h = 133.8 mg/L ( Rat ) 4 h
Butanone oxime	= 930 mg/kg ( Rat )	1000 - 1800 mg/kg ( Rabbit )	> 4.83 mg/L ( Rat ) 4 h
Stoddard solvent	-	> 3000 mg/kg ( Rabbit )	> 5.5 mg/L ( Rat ) 4 h
Carbon black	> 15400 mg/kg ( Rat )	-	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
Naphtha, petroleum, hydrotreated heavy	> 6000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	> 8500 mg/m <sup>3</sup> ( Rat ) 4 h
Benzaldehyde	= 1300 mg/kg ( Rat )	> 1250 mg/kg ( Rabbit )	-
Ethylbenzene	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	Causes skin irritation. Classification based on data available for ingredients.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation. Classification based on data available for ingredients.
<b>Respiratory or skin sensitization</b>	May cause an allergic skin reaction.
<b>Germ cell mutagenicity</b>	May cause genetic defects. Contains a known or suspected mutagen. Classification based on data available for ingredients.
<b>Carcinogenicity</b>	May cause cancer. Contains a known or suspected carcinogen. Classification based on data available for ingredients.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	A3	Group 2B	-	X
Ethanol 64-17-5	A3	Group 1	Known	X
Carbon black 1333-86-4	A3	Group 2B	-	X
Ethylbenzene 100-41-4	A3	Group 2B	-	X

#### Legend

##### ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

##### IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

##### NTP (National Toxicology Program)

Known - Known Carcinogen

##### OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

<b>Reproductive toxicity</b>	No information available.
<b>STOT - single exposure</b>	Causes damage to organs. Based on the classification criteria of the Globally Harmonized



System as adopted in the country or region with which this safety data sheet complies, this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE).

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard**

No information available.

**12. Ecological information****Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum distillates, hydrotreated light 64742-47-8	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss)	-	-
Solvent naphtha (petroleum), medium aliph. 64742-88-7	EC50: =450mg/L (96h, Pseudokirchneriella subcapitata)	LC50: =800mg/L (96h, Pimephales promelas)	-	EC50: >100mg/L (48h, Daphnia magna)
Ethanol 64-17-5	-	LC50: 12.0 - 16.0mg/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)	-	LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)
Butanone oxime 96-29-7	EC50: =83mg/L (72h, Desmodosmus subspicatus)	LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: =760mg/L (96h, Poecilia reticulata)	-	EC50: =750mg/L (48h, Daphnia magna)
Naphtha, petroleum, hydrotreated heavy 64742-48-9	-	LC50: =2200mg/L (96h, Pimephales promelas)	-	-
Benzaldahyde 100-52-7	-	LC50: 10.6 - 11.8mg/L (96h, Oncorhynchus mykiss) LC50: =12.69mg/L (96h, Oncorhynchus mykiss) LC50: 0.8 - 1.44mg/L (96h, Lepomis macrochirus) LC50: 6.8 - 8.53mg/L (96h, Pimephales promelas) LC50: =7.5mg/L (96h, Lepomis macrochirus)	-	-
Ethylbenzene 100-41-4	EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)

	(72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata)		
--	---	---	--	--

**Persistence and degradability** No information available.

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Ethanol 64-17-5	-0.35
Butanone oxime 96-29-7	0.65
Stoddard solvent 8052-41-3	6.4
Benzaldehyde 100-52-7	1.4
Ethylbenzene 100-41-4	3.6

**Other adverse effects** No information available.

## 13. Disposal considerations

### Disposal methods

**Waste from residues/unused products** Dispose of in accordance with local regulations, Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California waste information** This product contains one or more substances that are listed with the State of California as a hazardous waste.

## 14. Transport information

**DOT** Not regulated

**TDG** Not regulated

**IATA** Not regulated

**IMDG** Not regulated

## 15. Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**International Inventories**

Contact supplier for inventory compliance status

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Ethylbenzene - 100-41-4	0.1

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene 100-41-4	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethanol - 64-17-5	Carcinogen Developmental
Carbon black - 1333-86-4	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen
Quartz - 14808-60-7	Carcinogen
Toluene - 108-88-3	Developmental
Naphthalene - 91-20-3	Carcinogen
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Titanium dioxide 13463-67-7	X	X	X
Ethanol 64-17-5	X	X	X
Stoddard solvent 8052-41-3	X	X	X
Carbon black 1333-86-4	X	X	X
Benzaldehyde 100-52-7	X	X	X
Ethylbenzene 100-41-4	X	X	X
Cumene 98-82-8	X	X	X
Quartz 14808-60-7	X	X	X
Toluene 108-88-3	X	X	X
Naphthalene 91-20-3	X	X	X
Benzene 71-43-2	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. Other information**

<b>NFPA</b>	Health hazards 3	Flammability 0	Instability 0	Special hazards -
<b>HMIS</b>	Health hazards * 3	Flammability 0	Physical hazards 0	Personal protection X

Chronic Hazard Star Legend      \* = Chronic Health Hazard

**Key or legend to abbreviations and acronyms used in the safety data sheet****Legend Section 8: Exposure controls/personal protection**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

**Key literature references and sources for data used to compile the SDS**

U.S. Environmental Protection Agency ChemView Database  
 European Food Safety Authority (EFSA)  
 EPA (Environmental Protection Agency)  
 Acute Exposure Guideline Level(s) (AEGL(s))  
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
 U.S. Environmental Protection Agency High Production Volume Chemicals  
 Food Research Journal  
 Hazardous Substance Database  
 International Uniform Chemical Information Database (IUCLID)  
 Japan GHS Classification  
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)  
 NIOSH (National Institute for Occupational Safety and Health)  
 National Library of Medicine's ChemID Plus (NLM CIP)

National Toxicology Program (NTP)  
New Zealand's Chemical Classification and Information Database (CCID)  
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organization for Economic Co-operation and Development High Production Volume Chemicals Program  
Organization for Economic Co-operation and Development Screening Information Data Set  
World Health Organization

**Issuing Date** draft  
**Revision Date** 13-Oct-2023  
**Revision Note** Initial Release.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**