



SAFETY DATA SHEET

US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Issuing Date draft

Revision Date 13-Oct-2023

Revision Number 1

1. Identification

Product identifier

Product Name Java Gel Stain

Other means of identification

Product Code(s) B259

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Wood coating

Restrictions on use Use only for intended applications

Details of the supplier of the safety data sheet

Manufacturer Address

General Finishes
2462 Coporate Circle
East Troy, WI 53120
Phone 1-800-783-6050

Distributor

Wood Essence
2343 1st Ave North, unit B
Saskatoon, SK S7K 2A2
Phone 306-955-8775

Dover Finishing Products
180 Ave Du Voyageur
Pointe-Claire, QC H9R6A8
Phone 514-697-3000

Lee Valley Tools
1090 Morrison Drive
Ottawa, ON K2H1C2
Phone 613-596-0350

Emergency telephone number

Emergency telephone 24 Hour Emergency Phone Number
Chemtrec 1-800-424-9300
+1 703 527 3887 (CHEMTREC International)

2. Hazard(s) identification

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

Label elements**Danger****Hazard statements**

Causes skin irritation.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 May cause genetic defects.
 May cause cancer.
 Causes damage to organs.
 Causes damage to organs through prolonged or repeated exposure.

**Precautionary Statements - Prevention**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Use personal protective equipment as required.
 Wash face, hands and any exposed skin thoroughly after handling.
 Contaminated work clothing should not be allowed out of the workplace.
 Do not breathe dust, fume, gas, mist, vapors and spray.
 Do not eat, drink or smoke when using this product.

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

Skin

IF ON SKIN: Wash with plenty of soap and water.
 Take off contaminated clothing and wash before reuse.
 If skin irritation or rash occurs: Get medical advice and attention.

Precautionary Statements - Storage

Store locked up.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

Other information

No information available.

3. Composition/information on ingredients**Substance**

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review	Date HMIRA filed and date exemption
---------------	---------	----------	---------------------------------------	-------------------------------------

			Act registry number (HMIRA registry #)	granted (if applicable)
Petroleum distillates, hydrotreated light	64742-47-8	10 - 30	-	-
Solvent naphtha (petroleum), medium aliph.	64742-88-7	10 - 30	-	-
Stoddard solvent	8052-41-3	5 - 10	-	-
Ethanol	64-17-5	1 - 5	-	-
Carbon black	1333-86-4	1 - 5	-	-
2-Butanone, oxime	96-29-7	0.5 - 1.5	-	-
Xylene	1330-20-7	0.1 - 1	-	-
Talc	14807-96-6	0.1 - 1	-	-
Quartz	14808-60-7	0.1 - 1	-	-
Ethylbenzene	100-41-4	0.1 - 1	-	-
Benzaldehyde	100-52-7	0.1 - 1	-	-
Naphtha, petroleum, hydrotreated heavy	64742-48-9	0.1 - 1	-	-

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. If symptoms persist, call a physician. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.
Effects of Exposure	May cause cancer. Mutagenic effects. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure.

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

5. Fire-fighting measures

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	No information available.
Specific hazards arising from the chemical	Product is or contains a sensitizer. May cause sensitization by skin contact.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. Handling and storage**Precautions for safe handling**

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection**Control parameters****Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Xylene	TWA: 20 ppm	TWA: 100 ppm	-

1330-20-7		TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³		
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust	
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust	
Ethylbenzene 100-41-4	Ototoxicant - potential to cause hearing disorders TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	
Chemical name	Alberta	British Columbia	Ontario	Quebec
Stoddard solvent 8052-41-3	TWA: 100 ppm TWA: 572 mg/m ³	TWA: 290 mg/m ³ STEL: 580 mg/m ³	TWA: 525 mg/m ³	TWA: 100 ppm TWA: 525 mg/m ³
Ethanol 64-17-5	TWA: 1000 ppm TWA: 1880 mg/m ³	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
Carbon black 1333-86-4	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³
Xylene 1330-20-7	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³
Talc 14807-96-6	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
Quartz 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
Benzaldahyde 100-52-7	-	-	STEL: 4 ppm STEL: 17 mg/m ³	-

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Stoddard solvent	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
Ethanol	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm
Carbon black	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³
Xylene	TWA: 20 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 20 ppm	TWA: 20 ppm
Talc	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
Quartz	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³
Ethylbenzene	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Stoddard solvent	TWA: 100 ppm STEL: 125 ppm	TWA: 100 ppm	TWA: 100 ppm STEL: 125 ppm	TWA: 100 ppm TWA: 575 mg/m ³ STEL: 150 ppm STEL: 720 mg/m ³
Ethanol	TWA: 1000 ppm STEL: 1250 ppm	STEL: 1000 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 1000 ppm STEL: 1900 mg/m ³
Carbon black	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³
Xylene	TWA: 100 ppm STEL: 150 ppm	TWA: 20 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 650 mg/m ³ Skin
Talc	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 20 mppcf
Quartz	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.05 mg/m ³	TWA: 300 particle/mL
Ethylbenzene	TWA: 100 ppm STEL: 125 ppm Designated substance	TWA: 20 ppm	TWA: 100 ppm STEL: 125 ppm Designated Chemical Substance	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Biological occupational exposure limits

Chemical name	ACGIH
Xylene 1330-20-7	1.5 g/g creatinine - urine (Methylhippuric acids) - end of shift
Ethylbenzene 100-41-4	0.15 g/g creatinine - urine (Sum of mandelic acid and phenylglyoxylic acid) - end of shift

Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.
-----------------------------	---

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Hand protection	Wear suitable gloves. Impervious gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Physical state	Liquid
----------------	--------

Color	Black / Brown
Odor	Slight
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH		No data available
Melting point / freezing point		No data available
Initial boiling point and boiling range		No data available
Flash point		No data available
Evaporation rate		No data available
Flammability		No data available
Flammability Limit in Air		
Upper flammability or explosive limits		No data available
Lower flammability or explosive limits		No data available
Vapor pressure		No data available
Relative vapor density		No data available
Relative density	8.0	
Water solubility	Insoluble in water	
Solubility(ies)		No data available
Partition coefficient		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	900 - 1200 cP	
<u>Other information</u>		
Explosive properties	No information available.	
Oxidizing properties	No information available.	
Softening point	No information available	
Molecular weight	No information available	
VOC content	No information available	
VOC	< 450 g/L	
Liquid Density	No information available	
Bulk density	No information available	

10. Stability and reactivity

Reactivity	None under normal use conditions.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	None known based on information supplied.
Incompatible materials	Strong acids, Strong bases, Strong oxidizing agents.
Hazardous decomposition products	None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	May cause irritation of respiratory tract. Specific test data for the substance or mixture is not available.
-------------------	--

Eye contact	Causes serious eye irritation (based on components). May cause redness, itching, and pain. Specific test data for the substance or mixture is not available.
Skin contact	Causes skin irritation (based on components). Repeated exposure may cause skin dryness or cracking. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Specific test data for the substance or mixture is not available.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document:

ATEmix (oral)	9,254.20 mg/kg
ATEmix (dermal)	5,842.10 mg/kg
ATEmix (inhalation-vapor)	88.10 mg/l
ATEmix (inhalation-dust/mist)	15.9121 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Solvent naphtha (petroleum), medium aliph.	> 25 mL/kg (Rat)	> 4000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Stoddard solvent	-	> 3000 mg/kg (Rabbit)	> 5.5 mg/L (Rat) 4 h
Ethanol	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h
Carbon black	> 15400 mg/kg (Rat)	-	> 4.6 mg/m ³ (Rat) 4 h
2-Butanone, oxime	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h
Xylene	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Benzaldehyde	= 1300 mg/kg (Rat)	> 1250 mg/kg (Rabbit)	-
Naphtha, petroleum, hydrotreated heavy	> 6000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 8500 mg/m ³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Causes skin irritation. Classification based on data available for ingredients.
Serious eye damage/eye irritation	Causes serious eye irritation. Classification based on data available for ingredients.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	May cause genetic defects. Contains a known or suspected mutagen. Classification based

on data available for ingredients.

Carcinogenicity

May cause cancer. Contains a known or suspected carcinogen. Classification based on data available for ingredients.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethanol 64-17-5	A3	Group 1	Known	X
Carbon black 1333-86-4	A3	Group 2B	-	X
Xylene 1330-20-7	-	Group 3	-	-
Talc 14807-96-6	-	Group 3	-	X
Quartz 14808-60-7	A2	Group 1	Known	X
Ethylbenzene 100-41-4	A3	Group 2B	-	X

Legend**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

No information available.

STOT - single exposure

Causes damage to organs. Based on the classification criteria of the Globally Harmonized System as adopted in the country or region with which this safety data sheet complies, this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE).

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

No information available.

12. Ecological information**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum distillates, hydrotreated light 64742-47-8	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss)	-	-
Solvent naphtha (petroleum), medium aliph. 64742-88-7	EC50: =450mg/L (96h, Pseudokirchneriella subcapitata)	LC50: =800mg/L (96h, Pimephales promelas)	-	EC50: >100mg/L (48h, Daphnia magna)
Ethanol	-	LC50: 12.0 - 16.0mL/L	-	LC50: 9268 -

64-17-5		(96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)		14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)
2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, Desmodosmus subspicatus)	LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: =760mg/L (96h, Poecilia reticulata)	-	EC50: =750mg/L (48h, Daphnia magna)
Xylene 1330-20-7	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)
Talc 14807-96-6	-	LC50: >100g/L (96h, Brachydanio rerio)	-	-
Ethylbenzene 100-41-4	EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =9.6mg/L (96h, Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)
Benzaldahyde 100-52-7	-	LC50: 10.6 - 11.8mg/L (96h, Oncorhynchus mykiss) LC50: =12.69mg/L (96h, Oncorhynchus mykiss)	-	-

		LC50: 0.8 - 1.44mg/L (96h, Lepomis macrochirus) LC50: 6.8 - 8.53mg/L (96h, Pimephales promelas) LC50: =7.5mg/L (96h, Lepomis macrochirus)		
Naphtha, petroleum, hydrotreated heavy 64742-48-9	-	LC50: =2200mg/L (96h, Pimephales promelas)	-	-

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Stoddard solvent 8052-41-3	6.4
Ethanol 64-17-5	-0.35
2-Butanone, oxime 96-29-7	0.65
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.6
Benzaldehyde 100-52-7	1.4

Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused products Dispose of in accordance with local regulations, Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

California waste information This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT Not regulated

TDG Not regulated

IATA Not regulated

IMDG Not regulated

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture**International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

Contact supplier for inventory compliance status

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1.0
Ethylbenzene - 100-41-4	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X
Ethylbenzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Ethanol - 64-17-5	Carcinogen Developmental

Carbon black - 1333-86-4	Carcinogen
Quartz - 14808-60-7	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen
Toluene - 108-88-3	Developmental
Naphthalene - 91-20-3	Carcinogen
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Stoddard solvent 8052-41-3	X	X	X
Ethanol 64-17-5	X	X	X
Carbon black 1333-86-4	X	X	X
Xylene 1330-20-7	X	X	X
Iron oxide 1309-37-1	X	X	X
Magnesium carbonate 546-93-0	X	X	-
Talc 14807-96-6	X	X	X
Quartz 14808-60-7	X	X	X
Ethylbenzene 100-41-4	X	X	X
Benzaldehyde 100-52-7	X	X	X
Cumene 98-82-8	X	X	X
Toluene 108-88-3	X	X	X
Naphthalene 91-20-3	X	X	X
Benzene 71-43-2	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 3 Flammability 0 Instability 0 Special hazards -
HMIS Health hazards * 3 Flammability 0 Physical hazards 0 Personal protection X
Chronic Hazard Star Legend * = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: Exposure controls/personal protection
 TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
 Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
Japan GHS Classification
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Issuing Date draft

Revision Date 13-Oct-2023

Revision Note Initial Release.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet