



# SAFETY DATA SHEET

US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Issuing Date 10-May-2024

Revision Date 10-May-2024

Revision Number 1

## 1. Identification

### Product identifier

**Product Name** Neutral Primer (Tintable)

### Other means of identification

**Product Code(s)** B847

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended use** Wood coating

**Restrictions on use** Use only for intended applications

### Details of the supplier of the safety data sheet

#### Manufacturer Address

General Finishes  
2462 Coporate Circle  
East Troy, WI 53120  
Phone 1-800-783-6050

#### Distributor

Wood Essence  
2343 1st Ave North, unit B  
Saskatoon, SK S7K 2A2  
Phone 306-955-8775

Dover Finishing Products  
180 Ave Du Voyageur  
Pointe-Claire, QC H9R6A8  
Phone 514-697-3000

Lee Valley Tools  
1090 Morrison Drive  
Ottawa, ON K2H1C2  
Phone 613-596-0350

### Emergency telephone number

**Emergency telephone** 24 Hour Emergency Phone Number  
Chemtrec 1-800-424-9300  
+1 703 527 3887 (CHEMTREC International)

## 2. Hazard(s) identification

### Classification

Carcinogenicity

Category 1A

### Label elements

**Danger**

**Hazard statements**

May cause cancer.



#### Precautionary Statements - Prevention

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Use personal protective equipment as required.

#### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

#### Precautionary Statements - Storage

Store locked up.

#### Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

#### Other information

No information available.

### 3. Composition/information on ingredients

#### Substance

Not applicable.

#### Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Limestone	1317-65-3	15 - 40	-	-
Talc	14807-96-6	7 - 13	-	-
Kaolin	1332-58-7	5 - 10	-	-
Dipropylene glycol monomethyl ether	34590-94-8	0.5 - 1.5	-	-
2-Butoxyethanol	111-76-2	0.5 - 1.5	-	-
Quartz	14808-60-7	0.1 - 1	-	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First-aid measures

#### Description of first aid measures

<b>General advice</b>	IF exposed or concerned: Get medical advice/attention.
<b>Inhalation</b>	Remove to fresh air.
<b>Eye contact</b>	Rinse thoroughly with plenty of water, also under the eyelids.
<b>Skin contact</b>	Wash skin with soap and water.

Ingestion Rinse mouth.

**Most important symptoms and effects, both acute and delayed**

Symptoms Prolonged contact may cause redness and irritation.

Effects of Exposure May cause cancer.

**Indication of any immediate medical attention and special treatment needed**

Note to physicians Treat symptomatically.

## 5. Fire-fighting measures

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical No information available.

**Explosion data**

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures**

Personal precautions Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

**Methods and material for containment and cleaning up**

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. Handling and storage

**Precautions for safe handling**

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

**Conditions for safe storage, including any incompatibilities**

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

## 8. Exposure controls/personal protection

**Control parameters**

## Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH	
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	
Talc 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust	
Kaolin 1332-58-7	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust	
Dipropylene glycol monomethyl ether 34590-94-8	TWA: 50 ppm	TWA: 100 ppm TWA: 600 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 600 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 900 mg/m <sup>3</sup> (vacated) Sk* Sk*	IDLH: 600 ppm TWA: 100 ppm TWA: 600 mg/m <sup>3</sup> STEL: 150 ppm STEL: 900 mg/m <sup>3</sup>	
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) Sk* Sk*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>	
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust	
Chemical name	Alberta	British Columbia	Ontario	Quebec
Limestone 1317-65-3	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>	-	TWA: 10 mg/m <sup>3</sup>
Talc 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Kaolin 1332-58-7	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Dipropylene glycol monomethyl ether 34590-94-8	TWA: 100 ppm TWA: 606 mg/m <sup>3</sup> STEL: 150 ppm STEL: 909 mg/m <sup>3</sup> Sk*	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm Sk*	TWA: 100 ppm TWA: 606 mg/m <sup>3</sup> STEL: 150 ppm STEL: 909 mg/m <sup>3</sup> Skin

2-Butoxyethanol 111-76-2	TWA: 20 ppm TWA: 97 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Talc	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Kaolin	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Dipropylene glycol monomethyl ether	TWA: 50 ppm	TWA: 100 ppm STEL: 150 ppm Sk*	TWA: 50 ppm	TWA: 50 ppm
2-Butoxyethanol	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
Quartz	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Limestone	TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>		TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>	TWA: 30 mppcf TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
Talc	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 20 mppcf
Kaolin	TWA: 2 mg/m <sup>3</sup> STEL: 4 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup> STEL: 4 mg/m <sup>3</sup>	TWA: 30 mppcf TWA: 10 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>
Dipropylene glycol monomethyl ether	TWA: 100 ppm STEL: 150 ppm Sk*	TWA: 50 ppm	TWA: 100 ppm STEL: 150 ppm Skin	
2-Butoxyethanol	TWA: 20 ppm STEL: 30 ppm	TWA: 20 ppm	TWA: 20 ppm STEL: 30 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> STEL: 150 ppm STEL: 720 mg/m <sup>3</sup> Sk*
Quartz	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>	TWA: 300 particle/mL

### Biological occupational exposure limits

Chemical name	ACGIH
2-Butoxyethanol 111-76-2	200 mg/g creatinine - urine (Butoxyacetic acid with hydrolysis) - end of shift

### Appropriate engineering controls

<b>Engineering controls</b>	Showers Eyewash stations Ventilation systems.
-----------------------------	---

### Individual protection measures, such as personal protective equipment

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Hand protection</b>	Wear suitable gloves.
<b>Skin and body protection</b>	Wear suitable protective clothing.
<b>Respiratory protection</b>	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

#### Appearance

Physical state	Liquid
Color	Clear / Grey
Odor	Slight
Odor threshold	No information available

#### Property

#### Values

#### Remarks • Method

pH	7.5 - 8.5	
Melting point / freezing point		No data available
Initial boiling point and boiling range		No data available
Flash point		No data available
Evaporation rate		No data available
Flammability		No data available
Flammability Limit in Air		
Upper flammability or explosive limits		No data available
Lower flammability or explosive limits		No data available
Vapor pressure		No data available
Relative vapor density		No data available
Relative density	12.75	
Water solubility	Soluble in water	
Solubility(ies)		No data available
Partition coefficient		No data available
Autoignition temperature		No data available
Decomposition temperature		No data available
Kinematic viscosity		No data available
Dynamic viscosity	400 - 600 cP	

#### Other information

Explosive properties	No information available.
Oxidizing properties	No information available.
Softening point	No information available
Molecular weight	No information available
VOC content	< 50 g/L
Liquid Density	No information available
Bulk density	No information available

## 10. Stability and reactivity

Reactivity	None under normal use conditions.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Do not freeze.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	None known based on information supplied.

## 11. Toxicological information

**Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	Specific test data for the substance or mixture is not available.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms** Prolonged contact may cause redness and irritation.

**Acute toxicity****Numerical measures of toxicity**

Based on available data, the classification criteria are not met

The following values are calculated based on chapter 3.1 of the GHS document:

<b>ATEmix (oral)</b>	64,490.10 mg/kg
<b>ATEmix (dermal)</b>	54,568.50 mg/kg
<b>ATEmix (inhalation-vapor)</b>	86.50 mg/l
<b>ATEmix (inhalation-dust/mist)</b>	19.90 mg/l

**Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kaolin	> 5000 mg/kg ( Rat )	> 5000 mg/kg ( Rat )	-
Dipropylene glycol monomethyl ether	= 5.35 g/kg ( Rat )	= 9500 mg/kg ( Rabbit )	-
2-Butoxyethanol	= 1300 mg/kg ( Rat )	= 435 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h = 486 ppm ( Rat ) 4 h

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	No information available.
<b>Serious eye damage/eye irritation</b>	No information available.
<b>Respiratory or skin sensitization</b>	No information available.
<b>Germ cell mutagenicity</b>	No information available.
<b>Carcinogenicity</b>	May cause cancer. Contains a known or suspected carcinogen. Classification based on data available for ingredients.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6	-	Group 3	-	X
2-Butoxyethanol 111-76-2	A3	Group 3	-	-
Quartz	A2	Group 1	Known	X

14808-60-7

**Legend****ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**Occupational Safety and Health Administration of the US Department of Labor**

X - Present

**Reproductive toxicity** No information available.**STOT - single exposure** No information available.**STOT - repeated exposure** No information available.**Aspiration hazard** No information available.**12. Ecological information****Ecotoxicity** The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Talc 14807-96-6	-	LC50: >100g/L (96h, Brachydanio rerio)	-	-
Dipropylene glycol monomethyl ether 34590-94-8	-	LC50: >10000mg/L (96h, Pimephales promelas)	-	LC50: =1919mg/L (48h, Daphnia magna)
2-Butoxyethanol 111-76-2	-	LC50: =1490mg/L (96h, Lepomis macrochirus) LC50: =2950mg/L (96h, Lepomis macrochirus)	-	EC50: >1000mg/L (48h, Daphnia magna)

**Persistence and degradability** No information available.**Bioaccumulation****Component Information**

Chemical name	Partition coefficient
Dipropylene glycol monomethyl ether 34590-94-8	0.35
2-Butoxyethanol 111-76-2	0.81

**Other adverse effects** No information available.**13. Disposal considerations****Disposal methods****Waste from residues/unused products** Dispose of in accordance with local regulations, Dispose of waste in accordance with environmental legislation.**Contaminated packaging** Do not reuse empty containers.



## 14. Transport information

<u>DOT</u>	Not regulated
<u>TDG</u>	Not regulated
<u>IATA</u>	Not regulated
<u>IMDG</u>	Not regulated

## 15. Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

#### International Inventories

Contact supplier for inventory compliance status

#### US Federal Regulations

##### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

##### **SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

##### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

##### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

#### US State Regulations

##### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Quartz - 14808-60-7	Carcinogen
1,4-Dioxane - 123-91-1	Carcinogen

Ethylene oxide - 75-21-8	Carcinogen Developmental Female Reproductive Male Reproductive
--------------------------	---

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Limestone 1317-65-3	X	X	X
Talc 14807-96-6	X	X	X
Kaolin 1332-58-7	X	X	X
Dipropylene glycol monomethyl ether 34590-94-8	X	X	X
2-Butoxyethanol 111-76-2	X	X	X
Quartz 14808-60-7	X	X	X
(2-methoxymethylethoxy)propanol 34590-94-8	X	X	X
Diethylene glycol monobutyl ether 112-34-5	X	-	X
Ethylene oxide 75-21-8	X	X	X
1,4-Dioxane 123-91-1	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. Other information**

**NFPA** Health hazards 0      **Flammability** 0      **Instability** 0      **Special hazards** -  
**HMIS** Health hazards 0      **Flammability** 0      **Physical hazards** 0      **Personal protection** X

**Key or legend to abbreviations and acronyms used in the safety data sheet**

**Legend**  
 SVHC: Substances of Very High Concern for Authorization:  
 PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances  
 vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances  
 STOT: Specific Target Organ Toxicity  
 ATE: Acute Toxicity Estimate  
 LC50: 50% Lethal Concentration  
 LD50: 50% Lethal Dose

**Legend Section 8: Exposure controls/personal protection**  
 TWA      TWA (time-weighted average)  
 Ceiling      Maximum limit value  
 +      Sensitizers

STEL      STEL (Short Term Exposure Limit)  
 Sk\*      Skin designation

**Key literature references and sources for data used to compile the SDS**

U.S. Environmental Protection Agency ChemView Database  
European Food Safety Authority (EFSA)  
Environmental Protection Agency  
Acute Exposure Guideline Level(s) (AEGl(s))  
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
U.S. Environmental Protection Agency High Production Volume Chemicals  
Food Research Journal  
Hazardous Substance Database  
International Uniform Chemical Information Database (IUCLID)  
Japan GHS Classification  
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)  
NIOSH (National Institute for Occupational Safety and Health)  
National Library of Medicine's ChemID Plus (NLM CIP)  
U.S. National Toxicology Program (NTP)  
New Zealand's Chemical Classification and Information Database (CCID)  
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organization for Economic Co-operation and Development High Production Volume Chemicals Program  
Organization for Economic Co-operation and Development Screening Information Data Set  
World Health Organization

**Issuing Date** 10-May-2024

**Revision Date** 10-May-2024

**Revision Note** Initial Release.

**Disclaimer**

**The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.**

**End of Safety Data Sheet**